



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

## 1M (OFF 100M ROLL) X 30MM X 0.4MM VENEER EDGING P/G IN TASMANIAN OAK 286-172 BY CONSOLIDATED VENEERS



SKU	Option	Part #	Price
3073-25	Colour: Tasmanian Oak, Size: 30mm x 0.4mm, Qty: 100m	286-172	\$



Model	
Type	Edgebanding Tape - Veneer
SKU	3073-25
Part Number	286-172
Barcode	9313815383895
Brand	Consolidated Veneers
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg

A continuous roll of timber edging strengthened with cellulose backing paper (fleece) and face-sanded to an even thickness. Fleece Veneer is used throughout Australia and internationally for standard edging applications, softforming and profile wrapping. **Features:-**

Continuous roll form - optimizes edgebanding speed whilst minimizing offcuts and wastage as experienced with short veneer strips

Staggered finger joints - extra strength and near invisible joints

Fleece - strong cellulose backing eliminates splintering, splitting, cracking and breakage during edgebanding - no priming required

Face Sanded - ready for lacquering after edgebanding

Original natural veneer - no cheap substitutes from other species

Wide range - over 40 species in stock

Australian Made - all veneer edging is manufactured in Sydney, Australia

### Application:-

Fleece Veneer can be applied using a wide selection of equipment including hotmelt edgebanders (Click here for more details), hot air edgebanders for pre-glued tapes (click here for more details), ordinary household irons (for pregled stock), or by hand using contact adhesives (click here for more details).

Most edgebanders' trimming devices will cut Fleece Veneer cleanly without difficulty.

Fleece Veneer can also be trimmed easily using a sharp blade or handheld edge-trimmer (click here for more details).

For best results when applying unglued Fleece Veneer edging, we recommend Hot Melt Adhesive (click here for



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

more details).

**Range Options:-** Fleeced Veneer edging is available in a range of sizes listed below:

Standard widths: 22mm (all species)

Other widths: 30mm and 40mm

Standard roll sizes: Unglued - 100m Preglued - 50m & 100m

Standard thickness: 0.45mm - 0.65mm

Non Standard species: Minimum Order 300m - 500m apply

*Please note other widths are available upon request.* Iron-On Timber Veneer Sheets are also available in a limited range of 2440mm x 305mm and 1220mm x 305mm sizes. Please contact us for availability.