

50M ROLL OF YELLOW PAPER BACKED ABRASIVE PS 30 D BY KLINGSPOR



SKU	Option	Part #	Price
8704212	Grit: 120G, Colour: Yellow, Width of Roll: 100mm	252422	\$70
1041060	Grit: 180G, Colour: Yellow, Width of Roll: 100mm	252424	\$103
3099	Grit: 40G, Colour: Yellow, Width of Roll: 100mm	252415	\$80
3097	Grit: 60G, Colour: Yellow, Width of Roll: 100mm	252419	\$119
8704211	Grit: 80G, Colour: Yellow, Width of Roll: 100mm	252420	\$70

Model	
Type	Abrasive Roll
SKU	3099
Part Number	252415
Barcode	4014855100835
Brand	Klingspor
Country of Origin	
Manufactured in	Germany
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

PS 30 D - the perfect **yellow paper** backed abrasive roll for quick work on larger surfaces

The abrasive roll PS 30 D truly shines when used for fast stock removal on larger surfaces. Made of highly durable paper, the backing allows for surface sanding carried out either by hand or using a machine. This premium abrasive is recommended for processing

wood,
paint, varnish and filler and,
to some degree, metal.

Optimum cutting force thanks to tear resistance and increased aggressiveness

Distinguished by its **yellow paper**, the abrasive roll PS 30 D by Klingspor combines extraordinary tear resistance with superior grain sharpness. Its grain sharpness gives the abrasive extra aggressiveness, allowing for stock removal with a high cutting force, e.g. during **decorating** work. The user can strip a significant amount of material off the workpiece with every pass. This fast stock removal rate produces a rough surface. It is advisable to start with rough preparatory work before sanding with finer tools in several subsequent steps. While exceptionally tear-resistant, the D-weight **yellow paper** backing remains perfectly flexible. Users opting for the abrasive roll PS 30 D benefit from an excellent price-performance ratio.

Powerful, effective and fast

The abrasive roll PS 30 D processes wood and coatings made up of varnish or paint with extraordinary efficiency and speed. Its high grain sharpness makes it necessary for the user to sand with the grain when working on wood, e.g. during **decorating** work and **dry wall sanding**. When sanding against the grain of the wood, the user risks



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

breaking out chips, leaving behind deep gouges. The work is preceded by an inspection for loose areas using a knife or a putty knife. Removing the loose layers prior to the sanding process minimises the time and effort necessary to complete sanding later on. Sanding by hand does not require any additional tools. When used for surface sanding, the paper of the abrasive roll PS 30 D should be wrapped around a sanding block. A clamping device keeps the paper from shifting during use.

Properties

Bonding agent: Resin

Grain: Aluminium oxide

Coating: Semi-open

Backing: D-paper

Materials

Paint

Varnish

Filling compound

Wood

Metals

Applications

Automotive industry

Wood processing industry

Options

252419

252422

252415

252420

252424