

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

40MM X 0.4MM VENEER EDGING IN JARRAH BY CONSOLIDATED VENEERS





Model	
Туре	Edgebanding Tape - Veneer
SKU	3127-25
Part Number	232-780
Brand	Consolidated Veneers
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg



*Beyond Tools Custom Edging Service - Don't want a full roll?
Rolls can be cut into 25m Increments (ie. 25m, 50m, 75m) there is a \$6 Cut Fee which will be applicable to all Cut Roll
Requests - Please add to cart here if applicable.*
A continuous roll of timber edging strengthened with
cellulose backing paper (fleece) and face-sanded to an even
thickness. Fleeced Veneer is used throughout Australia and
internationally for standard edging applications, softforming
and profile wrapping.

Features:-

Continuous roll form – optimizes edgebanding speed whilst minimizing offcuts and wastage as experienced with short veneer strips

Staggered finger joints – extra strength and near invisible joints

Fleeced – strong cellulose backing eliminates splintering, splitting, cracking and breakage during edgebanding – no priming required

Face Sanded – ready for lacquering after edgebanding Original natural veneer – no cheap substitutes from other species

Wide range – over 40 species in stock Australian Made – all veneer edging is manufactured in Sydney, Australia

Application:-

Fleeced Veneer can be applied using a wide selection of equipment including hotmelt edgebanders (Click here for more details), hot air edgebanders for pre-glued tapes (click here for more details), ordinary household irons (for preglued stock), or by hand using contact adhesives (click here for more details).

A SEYOND

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

Most edgebanders' trimming devices will cut Fleeced Veneer cleanly without difficulty.

Fleeced Veneer can also be trimmed easily using a sharp blade or handheld edge-trimmer (click here for more details). For best results when applying unglued Fleeced Veneer edging, we recommend Hot Melt Adhesive (click here for more details).

Range Options:- Fleeced Veneer edging is available in a range of sizes listed below:

Standard widths: 22mm (all species)
Other widths: 30mm and 40mm

Standard roll sizes: Unglued – 100m Preglued – 50m &

100m

Standard thickness: 0.45mm - 0.65mm

Non Standard

Minimum Order 300m - 500m apply

species:

Millimani Oraci 300m - 300m appry

Please note other widths are available upon request. Iron-On Timber Veneer Sheets are also available in a limited range of 2440mm x 305mm and 1220mm x 305mm sizes. Please contact us for availability.

Options

234-913

232-780

234-913

232-780