

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

40MM X 0.4MM VENEER EDGING IN JARRAH BY CONSOLIDATED VENEERS





Model	
Туре	Edgebanding Tape - Veneer
SKU	3127-25
Part Number	232-780
Brand	Consolidated Veneers
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg



*Beyond Tools Custom Edging Service - Don't want a full roll?
Rolls can be cut into 25m Increments (ie. 25m, 50m, 75m) there is a \$6 Cut Fee which will be applicable to all Cut Roll
Requests - Please add to cart here if applicable.*
A continuous roll of timber edging strengthened with
cellulose backing paper (fleece) and face-sanded to an even
thickness. Fleeced Veneer is used throughout Australia and
internationally for standard edging applications, softforming
and profile wrapping.

Features:-

Continuous roll form – optimizes edgebanding speed whilst minimizing offcuts and wastage as experienced with short veneer strips

Staggered finger joints – extra strength and near invisible joints

Fleeced – strong cellulose backing eliminates splintering, splitting, cracking and breakage during edgebanding – no priming required

Face Sanded – ready for lacquering after edgebanding Original natural veneer – no cheap substitutes from other species

Wide range – over 40 species in stock Australian Made – all veneer edging is manufactured in Sydney, Australia

Application:-

Fleeced Veneer can be applied using a wide selection of equipment including hotmelt edgebanders (Click here for more details), hot air edgebanders for pre-glued tapes (click here for more details), ordinary household irons (for preglued stock), or by hand using contact adhesives (click here for more details).



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

Most edgebanders' trimming devices will cut Fleeced Veneer cleanly without difficulty.

Fleeced Veneer can also be trimmed easily using a sharp blade or handheld edge-trimmer (click here for more details). For best results when applying unglued Fleeced Veneer edging, we recommend Hot Melt Adhesive (click here for more details).

Range Options:- Fleeced Veneer edging is available in a range of sizes listed below:

Standard widths: 22mm (all species)
Other widths: 30mm and 40mm

Standard roll sizes: Unglued – 100m Preglued – 50m &

100m

Standard thickness: 0.45mm - 0.65mm

Staridard tillettiess. 0.15

Non Standard Minimum Order 300m – 500m apply

species:

Please note other widths are available upon request. Iron-On

Timber Veneer Sheets are also available in a limited range of 2440mm x 305mm and 1220mm x 305mm sizes. Please

contact us for availability.