



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

BSW INTERMEDIATE CHROME TAP BY BORDO



SKU	Option	Part #	Price
35363	Size: 1/2" x 12TPI	4228-1/2I	\$13.52
35799	Size: 1/4" x 20TPI	4228-1/4I	\$7.3
46304	Size: 1/8" x 40TPI	4228-1/8I	\$9.4
35360	Size: 3/16" x 24TPI	4228-3/16I	\$6.24
35643	Size: 3/8" x 16TPI	4228-3/8I	\$9.4
1539	Size: 5/16" x 18TPI	4228-5/16I	\$8.32
8600041	Size: 5/32" x 32TPI	4228-5/32I	\$9.4
8711549	Size: 7/16" x 14TPI	4228-7/16I	\$11.44

Model	
Type	Intermediate Tap
SKU	35363
Part Number	4228-1/2I
Barcode	9326518042402
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com



About this item:

Chrome Alloy BSW Intermediate Hand Tap.



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Used as thread chasers to clean an existing thread.

They can also be used to create a new female thread in non-ferrous metals and plastics.

Chrome alloy taps are not suitable for creating precision, safety or critical threads.

British Standard Whitworth has a thread angle of 55 degrees as opposed to 60 degrees in Metric and Unified threads.

This thread form was developed by Sir Joseph Whitworth in 1841.

The thread form has rounded roots and crests and is specified in BS84:1956.

The major diameter of external thread and pitch are specified by a simple numerical value (most commonly measured in millimetres).

Intermediate Taps have a lead of four threads and are used in most general purpose applications to cut a thread true to a pre-drilled pilot hole.

Options

4228-3/16I

4228-1/4I

4228-1/8I

4228-3/8I

4228-7/16I

4228-5/32I

4228-5/16I

4228-1/2I