

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

9/64" BRIGHT CARDED HSS JOBBER DRILL BIT 2006-9/64S BY BORDO



BORDO METRIC QUICK SILVER M2 HSS JOBBER DRILLS ANSI B94-11 118 ° Split Point (crankshaft point) Split point is self centering and reduces the need for end thrust. Friction at workpiece is reduced. 118 ^o point angles are ideal for use in materials such as mild steel and cast iron. The 118 ° point creates easily controlled chips which are wide and thin. **DRILL BIT SURFACE TREATMENT** Bright Finish Jobber Drills have no surface treatment and are supplied in the as-ground condition. These tools are suitable for general purpose use, particularly for non-ferrous applications. Specifications: Spindle Speed Stainless Steel RPM: 1071 Spindle Speed Tool Steel RPM:1606 Spindle Speed Cast Iron RPM:2141 Spindle Speed Malleable Iron RPM:2409 Spindle Speed Med. Carbon Steel RPM:2676 Spindle Speed Free Cutting Steel RPM: 3836 Spindle Speed Aluminium/Brass RPM: 5442 Spindle Speed Wood/Plastic RPM: 8119 Feed per revolution mm: 0.08



SKU	Option	Part #	Price
35650		2006-9/64S	\$3

Model	
Туре	Drill Bit
SKU	35650
Part Number	2006-9/64S
Barcode	9326518035671
Brand	Bordo
Size	9/64"
Technical - Main	
Flute Length	44mm
Workshop (Site) Info	
Flute Length	44mm
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg
Quantity Per Pack	1