



23 Exhibition Drive, Malaga Western Australia



Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

## 50MM HIGH SPEED MASONRY (HSM) CORE DRILL BIT CL50S BY ARMEG



SKU	Option	Part #	Price
37356		CL50S	\$148

Model	
Type	Core Drill Bit
SKU	37356
Part Number	CL50S
Barcode	5022081002549
Brand	Armeg
Size	50mm (2")
Technical - Main	
Diameter	50mm
Country of Origin	
Manufactured in	Sheffield, England
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

Gives versatility of core drilling from 25 to 110mm diameter. Speeds of up to 35% faster and with minimal breakthrough not normally associated with core drilling. Lightweight, thin wall design, weighing 50% less than traditional core drills, meets less resistance when cutting through masonry materials. More accurate holes can be drilled faster, and breakthrough minimised by drilling on rotation only mode, in softer materials. Great for plumbing and electrical applications in brick, block, masonry, etc. Only for SDS+ or Hex Driven machines. **High Speed Masonry Core can be used in:**

Heavy duty concrete  
General concrete  
Hard bricks  
Soft bricks  
Lightweight blocks  
Natural stone  
Constructional granite  
Limestone

### **Ideal when working on:**

Waste pipes  
Water feed pipes  
Cable entry / exit  
Flue passage  
Extractor fans  
Exhausts  
Dust extractor ducting



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

*DID YOU KNOW? The HSM range was originally produced in response to greater use of lighter masonry building material where Professional Heavy Duty Core cans be overly powerful. Their popularity rocketed when SDS Plus hammer drills became industry standard.* **Technical Tip:-**

When cleanliness of breakout is critical, turn off hammer action and use 'rotary only' mode for the last part of the drilling process

**Recommended Speed:-**

Recommended speed for these cores is largely governed by the power tool itself. This is because they are designed to be used in power tools where in the majority of cases there is no facility to regulate the speed (SDS Plus, SDS Max machines etc.).

If used in a machine where speed regulation is possible, a general recommendation is the larger diameter of the core drill being used, the slower the speed.

**Material Chart:- Technical Data:-**

[View Technical Data Sheet Here](#)

**Machine Recommendations:-**