



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

200MM HIGH SPEED MASONRY (HSM) TOMMY BAR SUIT CORE DRILL BIT CLTB BY ARMEG



SKU	Option	Part #	Price
37360		CLTB	\$24



Model	
Type	Pilot Drill Bit (suit Core Drill Bit)
SKU	37360
Part Number	CLTB
Barcode	5022081003478
Brand	Armeg
Country of Origin	
Manufactured in	Sheffield, England
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg



Gives versatility of core drilling from 25 to 110mm diameter. Speeds of up to 35% faster and with minimal breakthrough not normally associated with core drilling. Lightweight, thin wall design, weighing 50% less than traditional core drills, meets less resistance when cutting through masonry materials. More accurate holes can be drilled faster, and breakthrough minimised by drilling on rotation only mode, in softer materials. Great for plumbing and electrical applications in brick, block, masonry, etc. Only for SDS+ or Hex Driven machines. **High Speed Masonry Core can be used in:**

Heavy duty concrete
General concrete
Hard bricks
Soft bricks
Lightweight blocks
Natural stone
Constructional granite
Limestone

Ideal when working on:

Waste pipes
Water feed pipes
Cable entry / exit
Flue passage
Extractor fans
Exhausts



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Dust extractor ducting

*DID YOU KNOW? The HSM range was originally produced in response to greater use of lighter masonry building material where Professional Heavy Duty Core cans be overly powerful. Their popularity rocketed when SDS Plus hammer drills became industry standard. **Technical Tip:-***

When cleanliness of breakout is critical, turn off hammer action and use 'rotary only' mode for the last part of the drilling process

Recommended Speed:-

Recommended speed for these cores is largely governed by the power tool itself. This is because they are designed to be used in power tools where in the majority of cases there is no facility to regulate the speed (SDS Plus, SDS Max machines etc.).

If used in a machine where speed regulation is possible, a general recommendation is the larger diameter of the core drill being used, the slower the speed.

Material Chart:- Technical Data:-

[View Technical Data Sheet Here](#)

Machine Recommendations:-