



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

## UNC TAPER CHROME TAP BY BORDO



SKU	Option	Part #	Price
401419	Size: 1" x 8TPI	4232-1T	\$48
9500856	Size: 12G x 24TPI	4232-12GT	\$9

Model	
Type	Taper Tap
SKU	401419
Part Number	4232-1T
Barcode	9326518043393
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)



**About this product:**

Chrome Alloy UNC Taper Hand Tap.



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

Used as thread chasers to clean an existing thread.

They can also be used to create a new female thread in non-ferrous metals and plastics.

Chrome alloy taps are not suitable for creating precision, safety or critical threads.

Unified National Coarse thread form was introduced in 1948 as an attempt to standardise thread forms in the USA, Canada and the UK.

The thread profile of UNC is the same as for metric threads and is described in the JIS B0206 standard.

The thread is described by its major diameter and the number of threads per inch of length (TPI).

This thread series is commonly used in the mass production of bolts, screws and nuts.

It is used for threading into lower tensile strength materials (bronze, brass, aluminium and plastics) to obtain the best resistance to stripping of the internal thread.

It is also used on quick assembly or disassembly or if corrosion or slight damage is possible.

Taper Taps have a lead of eight threads and are used as a starting tap in difficult or high precision holes.