



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

UNC INTERMEDIATE CHROME TAP BY BORDO



SKU	Option	Part #	Price
401420	Size: 1" x 8TPI	4232-1I	\$40.6
9500858	Size: 12G x 24TPI	4232-12GI	\$8.32

Model	
Type	Intermediate Tap
SKU	401420
Part Number	4232-1I
Barcode	9326518043560
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com



About this product:

Chrome Alloy UNC Intermediate Hand Tap.



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Used as thread chasers to clean an existing thread.

They can also be used to create a new female thread in non-ferrous metals and plastics.

Chrome alloy taps are not suitable for creating precision, safety or critical threads.

Unified National Coarse thread form was introduced in 1948 as an attempt to standardise thread forms in the USA, Canada and the UK.

The thread profile of UNC is the same as for metric threads and is described in the JIS B0206 standard.

The thread is described by its major diameter and the number of threads per inch of length (TPI).

This thread series is commonly used in the mass production of bolts, screws and nuts.

It is used for threading into lower tensile strength materials (bronze, brass, aluminium and plastics) to obtain the best resistance to stripping of the internal thread.

It is also used on quick assembly or disassembly or if corrosion or slight damage is possible.

Intermediate Taps have a lead of four threads and are used in most general purpose applications to cut a thread true to a pre-drilled pilot hole.