



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

## 1" X 8 UNC BOTTOMING CHROME TAP - 4232-1B BY BORDO



SKU	Option	Part #	Price
401421		4232-1B	\$44.72

Model	
Type	Bottoming Tap
SKU	401421
Part Number	4232-1B
Barcode	9326518043737
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)



**About this product:**

1" x 8 UNC Bottoming Chrome Tap



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

Chrome Alloy UNC Bottoming Hand Tap.

Used as thread chasers to clean an existing thread.

They can also be used to create a new female thread in non-ferrous metals and plastics.

Chrome alloy taps are not suitable for creating precision, safety or critical threads.

Unified National Coarse thread form was introduced in 1948 as an attempt to standardise thread forms in the USA, Canada and the UK.

The thread profile of UNC is the same as for metric threads and is described in the JIS B0206 standard.

The thread is described by its major diameter and the number of threads per inch of length (TPI).

This thread series is commonly used in the mass production of bolts, screws and nuts.

It is used for threading into lower tensile strength materials (bronze, brass, aluminium and plastics) to obtain the best resistance to stripping of the internal thread.

It is also used on quick assembly or disassembly or if corrosion or slight damage is possible.

Bottoming Taps have a lead of two threads and are used to ensure minimum thread run-out when tapping to the bottom of a blind hole.

Bottoming Taps are typically preceded by the use of a Taper or Intermediate Tap.