

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

1M (OFF 100M ROLL) X 22MM X 0.4MM VENEER EDGING P/G IN WESTERN RED CEDAR BY CONSOLIDATED VENEERS



SKU	Option		Part #	Price	
41134	Colour: Western Red Cedar, Size: 22mm 0.4mm, Qty: 100m	ıх	VENEER*WR*22PG	\$1.11	
Model					
Туре		Edgebanding Tape - Veneer			
SKU		41134			
Part Number		VENEERWR22PG			
Brand		Consolidated Veneers			
Technical - Main					
Edging - Base Material		Natural Veneer			
Edging - Surface		Veneer (Natural Timber)			
Edging - Unglued / Preglued		P/G (Pre Glued)			
Edging Width		21	21-22mm		
Country of Origin					
Manufactured in		Αι	Australia		
Packaging + Shipping					
Shipping Weight (Gross)		1.	1.48 kg		

A continuous roll of timber edging strengthened with

cellulose backing paper (fleece) and face-sanded to an even thickness. Fleeced Veneer is used throughout Australia and internationally for standard edging applications, softforming and profile wrapping. **Features:-**

Continuous roll form – optimizes edgebanding speed whilst minimizing offcuts and wastage as experienced with short veneer strips

Staggered finger joints – extra strength and near invisible joints

Fleeced – strong cellulose backing eliminates splintering, splitting, cracking and breakage during edgebanding – no priming required

Face Sanded – ready for lacquering after edgebanding Original natural veneer – no cheap substitutes from other species

Wide range – over 40 species in stock

Australian Made – all veneer edging is manufactured in Sydney, Australia

Application:-

Fleeced Veneer can be applied using a wide selection of equipment including hotmelt edgebanders (Click here for more details), hot air edgebanders for pre-glued tapes (click here for more details), ordinary household irons (for preglued stock), or by hand using contact adhesives (click here for more details).

Most edgebanders' trimming devices will cut Fleeced Veneer cleanly without difficulty.

Fleeced Veneer can also be trimmed easily using a sharp blade or handheld edge-trimmer (click here for more details). For best results when applying unglued Fleeced Veneer edging, we recommend Hot Melt Adhesive (click here for



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

more details).

Range Options:- Fleeced Veneer edging is available in a

range of sizes listed below:				
Standard widths:	22mm (all species)			
Other widths:	30mm and 40mm			
Standard roll sizes:	Unglued - 100m Preglued - 50m & 100m			
Standard thickness:	0.45mm – 0.65mm			
Non Standard species:	Minimum Order 300m – 500m apply			

Please note other widths are available upon request. Iron-On Timber Veneer Sheets are also available in a limited range of 2440mm x 305mm and 1220mm x 305mm sizes. Please contact us for availability.