

## 23 Exhibition Drive, Malaga Western Australia


Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

## 1M (OFF 100M ROLL) X 30MM X 0.4MM VENEER EDGING U/G IN TEAK 286-516 BY CONSOLIDATED VENEERS









A continuous roll of timber edging strengthened with cellulose backing paper (fleece) and face-sanded to an even thickness. Fleeced Veneer is used throughout Australia and internationally for standard edging applications, softforming and profile wrapping. **Features:-**

Continuous roll form – optimizes edgebanding speed whilst minimizing offcuts and wastage as experienced with short veneer strips

Staggered finger joints – extra strength and near invisible joints

Fleeced – strong cellulose backing eliminates splintering, splitting, cracking and breakage during edgebanding – no priming required

Face Sanded – ready for lacquering after edgebanding Original natural veneer – no cheap substitutes from other species

Wide range – over 40 species in stock Australian Made – all veneer edging is manufactured in Sydney, Australia

## Application:-

Fleeced Veneer can be applied using a wide selection of equipment including hotmelt edgebanders (Click here for more details), hot air edgebanders for pre-glued tapes (click here for more details), ordinary household irons (for preglued stock), or by hand using contact adhesives (click here for more details).

Most edgebanders' trimming devices will cut Fleeced Veneer cleanly without difficulty.

Fleeced Veneer can also be trimmed easily using a sharp blade or handheld edge-trimmer (click here for more details). For best results when applying unglued Fleeced Veneer edging, we recommend Hot Melt Adhesive (click here for



## 23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

more details).

Range Options:- Fleeced Veneer edging is available in a

range of sizes listed below:

Standard widths: 22mm (all species) Other widths: 30mm and 40mm

Unglued - 100m Preglued - 50m &

Standard roll sizes: 100m

Standard thickness: 0.45mm - 0.65mm

Non Standard

Minimum Order 300m - 500m apply

species:

Please note other widths are available upon request. Iron-On Timber Veneer Sheets are also available in a limited range of 2440mm x 305mm and 1220mm x 305mm sizes. Please

contact us for availability.

**Options** 

286-516

286-516