

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

28MM X 920MM SDS MAX 4-CUT DRILL BIT 4932352781 BY MILWAUKEE



| SKU | Option | Part # | Price |
|---------|--------|------------|---------|
| 5001027 | | 4932352781 | \$172.3 |



| Model | |
|-------------------------|---------------|
| Туре | Bit |
| SKU | 5001027 |
| Part Number | 4932352781 |
| Barcode | 4002395374397 |
| Brand | Milwaukee |
| Packaging + Shipping | |
| Shipping Weight (Gross) | 1.48 kg |

Features:

Especially developed robust head geometry with optimum 4 \times 90 ° symmetry of carbide tip: Reduces jamming up on hitting reinforcing steel.

Centring point with 130 $^{\circ}$ point angle: Easy spot drilling with pinpoint accuracy and ensures optimum guidance during drilling.

Robust secondary cutter with dynamic curved cutting edge: Supports the primary cutter for faster drilling.

Shorter spiral windings: This allows for faster transport of drilling dust from the head to the flute = Less wear and heat build-up at the tip.

Unique carbide tip: With more carbide on all diameters and extra carbide on $\tilde{A}_{\lrcorner}>32\text{mm}.$

Wear mark on both sides of primary cutter: Guarantees diameter accuracy (i.e. for anchor fittings) and acts as a life time indicator in warranty cases.

Deep flute shoulders: High volume dust removal for optimum drilling

Less wear and heat build-up.

Low vibration drilling performance: Comfortable drilling ensures less stress for man and machine.

Special surface treatment: Shot blasting provides a smooth surface and densifies the surface structure and makes the bit more wear resistant.

PGM Conformity: Guarantees precise holes for anchor fitting over the entire life time of the drill bit.