

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

48MM SDS-MAX COMBINATION HAMMER D25733K-XE BY DEWALT

\$1349 inc. GST





Model	
SKU	5008803
Part Number	D25733K-XE
Barcode	5035048667200
Brand	Dewalt
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

Features:

Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 48 mm in diameter. Core drilling up to 125 mm

Active vibration control system incorporating a counterbalance mass and floating handle delivers extremely low vibration

An anti rotation system detects a loss of tool control, and reacts by instantly cutting the power

Overview:

Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 48 mm in diameter. Core drilling up to 125 mm $\,$

Active vibration control system incorporating a counterbalance mass and floating handle delivers extremely low vibration

An anti rotation system detects a loss of tool control, and reacts by instantly cutting the power

Electronic speed and impact energy control

Lock-on switch for chipping

Rotation-stop for demolition applications in brick, masonry and light chasing in concrete

Brush wear and service indicators

Includes:

Multi-position side handle Heavy duty carrying case

Specifications:

Power Input 1600 Watts
Power Output 0 Watt
Impact energy (EPTA 05/2009) 13.3 J
Load Speed 177-355 rpm

177-355 rpm 1350-2705

Blows per Minute bp

bpm



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm



Max. Drilling Capacity [Concrete] 48 mm

Max. Drilling Capacity [Breakthrough bit] 80 mm

Max. Drilling Capacity [Core bit] 125 mm

Weight 9.3 kg

Weight (incl. battery)

Length 544 mm

Height 292 mm

Width 115 mm

Hand/Arm Vibration - Hammer drilling into concrete

Uncertainty K 1 (Vibration) 1.5 m/s ²

Hand/Arm Vibration - Chiselling 9.0 m/s ²

Uncertainty K 2 (Vibration) 1.5 m/s ²