

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

1700W 52MM SDS-MAX COMBINATION HAMMER WITH ANTI ROTATION D25773K BY DEWALT



THE REAL PROPERTY OF

SKU	Option	Part #		Price
5008805		D25773K-XE		\$1679
Model				
Туре			Rotary Hammer	
SKU			5008805	
Part Number			D25773K-XE	
Barcode			5054905244521	
Brand			Dewalt	
Size			52mm	
Dimensions				
Product Length			591 mm	
Product Width			115 mm	
Product Height			292 mm	
Product Weight (Net Weight)			10.5 kg	
Packaging + Ship	oing			
Shipping Weight (Gross)			10.0 kg	

Features

Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 52 mm in diameter. Core drilling up to 150 mm

Active vibration control system incorporating a

counterbalance mass and floating handle delivers extremely low vibration

An anti rotation system detects a loss of tool control, and reacts by instantly cutting the power

Overview

Ideal for drilling anchor fixing and through holes in concrete and masonry from 12 to 52 mm in diameter. Core drilling up to 150 mm

Active vibration control system incorporating a

counterbalance mass and floating handle delivers extremely low vibration

An anti rotation system detects a loss of tool control, and reacts by instantly cutting the power

Electronic variable speed and impact energy control

Lock-on switch for chipping

Rotation-stop for demolition applications in brick, masonry

and light chasing in concrete

Brush wear and service indicators

Includes

Multi-position side handle Heavy duty carrying case

Specifications:

Power Input	1700 Watts
Impact energy (EPTA 05/2009)	19.4 J
Load Speed	145-290 rpm
Blows per Minute	1105-2210



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 <u>hello@beyondtools.com</u>

	bpm
Max. Drilling Capacity [Concrete]	52 mm
Max. Drilling Capacity [Breakthrough bit]	80 mm
Max. Drilling Capacity [Core bit]	150 mm
Weight	10.5 kg
Weight (incl. battery)	
Length	591 mm
Height	292 mm
Width	115 mm
Hand/Arm Vibration - Hammer drilling into concrete	0 m/s ²
Uncertainty K 1 (Vibration)	1.5 m/s ²
Hand/Arm Vibration - Chiselling	0 m/s ²
Uncertainty K 2 (Vibration)	1.5 m/s ²
Sound Pressure	0 dB(A)
Sound Pressure Uncertainty	3 dB(A)
Sound Power	0 dB(A)
Sound Power Uncertainty	4 dB(A)