

4PCE 18V 5.0AH BRUSHLESS CORDLESS COMBO KIT DLX4136TX1 BY MAKITA



SKU	Option	Part #	Price
5009882		DLX4136TX1	\$1199

Model	
Type	Combo Kit
SKU	5009882
Part Number	DLX4136TX1
Barcode	088381723497
Brand	Makita
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

**Includes:**

Makita DHP481Z - 18v Li-ion Cordless Brushless Hammer

Driver Drill Skin

Makita DTD154Z - 18V 4-Mode Cordless Brushless Impact

Driver Skin

Makita DGA505Z - 18V 125mm Brushless Angle Grinder Skin

Makita DHR242Z - 18V 24mm Cordless Brushless Rotary

Hammer Drill Skin

Makita DX06 - 18V HEPA Dust Extraction System Attachment

to suit DHR242 Rotary Hammer 199566-6

2 x Makita BL1850B-L - 18V 5.0Ah Lithium Batteries with

Charge Indicator

1 x Makita DC18RC - 18V Active 3 Li-Ion Charger 195589-2

199935-1 - Tool Bag

Makita DHP481Z - 18v Li-ion Cordless Brushless Hammer

Driver Drill Skin

Features:

Single sleeve keyless chuck.

Mode ring selection.

Mechanical 2 speed gearing.

Twin LED job light with after-glow function.

Battery fuel gauge shows power remaining in battery.

Long rigid side grip helps to stabilize the bit for steady drilling/screwdriving.

All metal gear construction.

Wider torque range of 1 - 10Nm in clutch mode allows for versatile applications.

Single sleeve keyless chuck allows for easy bit installation/removal by one hand.

High performance Brushless DC motor. Produces more work amount on a single battery charge while also being durable against long continuous operation.



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Extreme Protection Technology with enhanced dust and drip resistant performance.

Specifications:

Voltage: 18V

Impacts Per Minute

Hi: 0 - 31,000ipm

Lo: 0 - 8,250ipm

Max Fastening Torque:

Hard: 115Nm

Soft: 60Nm

No Load Speed:

Hi: 0 - 2,100rpm

Lo: 0 - 550rpm

Capacity:

Masonry: 16mm

Steel: 13mm

Wood: 76mm

Dimensions (L x W x H): 205mm x 79mm x 249mm

Weight: 2kg

Makita DTD154Z - 18V 4-Mode Cordless Brushless Impact

Driver Skin

Features:

Brushless motor for more power and longer runtimes.

Aluminium hammer case.

One touch bit installation.

Electronic 3 stage impact selection.

T:mode for self drilling screws.

Variable speed control by trigger.

Ergonomically designed handle.

Specifications:

Voltage: 18V

Impacts per minute:

Speed 1: 0 - 3800ipm

Speed 2: 0 - 2600ipm

Speed 3: 0 - 1100ipm

Vibration level: 12.5m/s²

Sound pressure level: 96dB(A)

Sound power level: 107dB(A)

No load speed:

Speed 1: 0 - 3600rpm

Speed 2: 0 - 2100rpm

Speed 3: 0 - 1100rpm

Capacity:

Machine screw: M4 - M8

Standard bolt: M5 - M16

High strength bolt: M5 - M14

Coarse thread (length): 22mm - 125mm

Max fastening torque: 175Nm

Dimensions (L x W x H): 117mm x 79mm x 236mm

Weight: 1.2kg

Makita DGA505Z - 18V 125mm Brushless Angle Grinder Skin

Features:

Powerful Brushless DC motor (BLDC)

Paddle switch

Automatic Torque Drive - changes the cutting speed to load condition for an optimum operation

Battery fuel gauge

Gear housing can be rotated to suit most cutting and grinding applications

Anti-restart function prevents accidental start-up



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Concrete cutting depth of 20mm

Extreme Protection Technology with enhanced dust and drip resistant performance

Compatible with 1.5, 3.0, 4.0 and 5.0Ah Lithium-Ion batteries

Specifications:

Net Weight: 2.5kg

No Load Speed: 8,500rpm

Overall Length: 362mm

Wheel Size: 125 x 22mm

Makita DHR242Z - 18V 24mm Cordless Brushless Rotary

Hammer Drill Skin

Features:

Brushless DC motor helps to reduce energy loss by 30%

One-touch sliding SDS Plus type chuck

Variable speed control by trigger

Torque limiter

Easy to grip handle ergonomically designed to provide a sure and comfortable grip in any application

Natural position on mode selector provides 40 different bit angle settings

3 mode operation: Rotation+Hammering, Hammering only, Rotation only

Unique rubber joint construction suppresses the transmission of vibration to battery terminals, minimising battery failures

The tool body is separated into the upper and lower housings with vibration absorbing cushion rubbers

Compatible with 1.5, 3.0, 4.0 and 5.0Ah Lithium-Ion batteries

Specifications:

Drive Shank - SDS Plus Type

Impact Rate - 0-4,700ipm

Joules - 2.0J

Net Weight - 3.3kg

No Load Speed - 0-950rpm

Overall Length - 328mm

Capacity

Concrete - 24mm

Steel - 13mm

Wood - 27mm

Vibration m/s² - 13.5

Voltage - 18V

Makita DX06 - 18V HEPA Dust Extraction System Attachment to suit DHR242 Rotary Hammer 199566-6

Features:

Impact filter cleaning mechanism - Turn the dial to impact the filter case releasing the dust from the filter.

Built-in dual LED lights - To illuminate the work area with 10-second afterglow.

HEPA filtration system - Captures 99.97% of concrete dust particulates 0.3 microns and larger.

2 Stage Dust Extraction Nozzle - Stage 1 drill bits 110mm to 165mm / Stage 2 drill bits 210mm to 265mm.

Adjustable depth stop with 5mm increments

DX Extractors - Powered by a separate motor allowing the rotary hammer to maintain peak drilling performance.

Specifications:

Voltage: 18V

Weight: 1.3kg

Makita BL1850B-L - 18V 5.0Ah Lithium Battery with Charge

Indicator

Features:



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Fuel gauge indicator, displays charge remaining on battery in four stages

Built in memory chip communicates the usage history with the charger

Built in shock absorbers protect the cells from jobsite conditions

High energy cells pack more power per cell to reduce number of cells and overall weight

Large release button for easy removal from the tool

Built in air vents and wall cools the battery cells evenly whilst blocking damaging debris

16 contact terminals provide consistent power and firm hold in any environment

Specifications:

Cell Capacity: 5.0Ah

Charge Time: 45mins w/DC18RC

Net Weight: 630g

Voltage: 18V

Makita DC18RC - 18V Active 3 Li-Ion Charger 195589-2

Features:

Fast charging - charges Li-Ion 3.0Ah battery in only 22 minutes

Built-in CPU - gathers information from the battery's memory chip to determine optimum charging method

Forced air cooling fan - cools the battery to minimise charging time

Digital power display identifies the condition of the battery and charging condition

Specifications:

Voltage: 18V

Cell capacity: 1.5Ah - 6.0Ah

Charge Time:

1.5Ah: 15mins

3.0Ah: 22mins

4.0Ah: 36mins

5.0Ah: 45mins

6.0Ah: 55mins

Length: 185mm

Weight: 0.82kg