


## 18V FUEL PACKOUT WET/DRY L CLASS VACUUM BARE (TOOL ONLY) M18FPOVCL-0 BY MILWAUKEE



SKU	Option	Part #	Price
5011655		M18FPOVCL-0	\$365

Model	
Type	Wet / Dry Vacuum
SKU	5011655
Part Number	M18FPOVCL-0
Barcode	4892210198105
Brand	Milwaukee
Technical - Main	
Battery Voltage (V)	18V
Dimensions	
Product Length	434 mm
Product Width	267 mm
Product Height	325 mm
Product Weight (Net Weight)	5.1 kg
Packaging + Shipping	
Shipping Weight (Gross)	6.0 kg



The M18 FUEL™ PACKOUT™ Wet/Dry Vacuum L Class provides powerful suction and low noise, while being fully compatible with the Milwaukee PACKOUT™ Modular Storage System. A POWERSTATE™ Brushless motor delivers maximum suction for powerful performance to easily clean common wet and dry jobsite debris. PACKOUT™ compatibility gives the wet/dry vacuum unmatched mobility, saving the user time spent hauling tools on and off the jobsite. Bringing PACKOUT™ portability to jobsite clean up, the vacuum can be used either integrated within the PACKOUT™ stack or when removed from the stack. At just 87 dB(A), the M18 FUEL™ PACKOUT™ vacuum is suitable for use in occupied spaces. With 9.5 Litre dry capacity, the vacuum also includes a certified HEPA filter for optimal dust and microparticle collection, as well as a power tool adapter for efficient dust collection from other power tools. Part of the M18™ System, when powered by an M18™ REDLITHIUM™ -ION HIGH OUTPUT 8.0Ah Battery Pack (sold separately), the vacuum can deliver up to 30 minutes of runtime in high mode and over 50 minutes in low mode. **Features:**

- POWERSTATE™ Brushless Motor
- 1,416 l/min air flow (50 CFM)
- 117 mbar (1,194 mmH<sub>2</sub>O) water lift provides suction for wet and dry applications
- Fully compatible with PACKOUT™ Modular Storage System
- Sound power level of 87 dB(A)



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

On-board accessory storage

9.5 L dry capacity

Built-in blower port

High/low switch

**Specifications:**

Run Time: Up to 50 minutes (M18HB8)

Max Air Flow: 1,416 l/min (50 CFM)

Sealed Suction in Water: 117 mbar (1,194 mmH<sub>2</sub>O)

Diameter: 31.8 mm (1-1/4") (Inlet Diameter)

Wet Capacity: 6.5 L

Dry Capacity: 9.5 L

**Includes:**

(1) M18 FUEL™ PACKOUT™ Wet/Dry Vacuum L Class  
(M18FPOVCL-0)

(1) Utility Nozzle

(1) Crevice Tool

(1) 1.8 m Flexible Hose

(1) HEPA Filter

(1) Power Tool Adapter

(Not Included) Battery & Charger

**Resources:**

General Power Tool Safety Warning

Operator's Manual (M18FPOVCL-0)