

## 18V BRUSHLESS LTX CLASS DRILL/SCREWDRIVER - 602358850 BY METABO



SKU	Option	Part #	Price
5011704		602358850	\$375

Model	
Type	Hand Tools
SKU	5011704
Part Number	602358850
Barcode	4061792188136
Brand	Metabo
Packaging + Shipping	
Shipping Weight (Gross)	3.3 kg



### FEATURES

Brushless drill/screwdriver with maximum power for demanding applications

Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces

Powerful Brushless motor for greatest efficiency and long battery pack runtime

Precision Stop: electronic torque control with increased precision for accurate and intricate working

Overload protection: protects the motor from overheating

Euro collar (Ø 43 mm) for versatile use

Electronic safety shutdown: no kickback if the drill bit stops unexpectedly - for high user safety

Integrated LED work light with afterglow function for optimal brightness in the work area

With handy belt hook and bit case which can be fixed either on the right or left side

Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: [www.cordless-alliance-systems.com](http://www.cordless-alliance-systems.com)

### SPECIFICATIONS

#### Characteristics

Battery voltage - 18 V

Maximum torque, soft - 65 Nm / 575 ft. lbs

Pulse torque - 65 Nm / 575 in-lbs

Maximum torque, hard - 130 Nm / 1151 ft. lbs

Adjustable torque - 1 - 20 Nm // 9 - 177 in-lbs

Drill Ø steel - 13 mm / 1/2 "

Drill-Ø soft wood - 68 mm / 2.68 "

No-load speeds - 0 - 550 / 0 - 2000 rpm

Chuck capacity - 1.5 - 13 mm // 1/16 - 1/2 "

Collar diameter - 43 mm / 1 11/16 "

Weight without battery pack - 1.7 kg / 3.7 lbs

Weight with battery pack - 2.2 kg / 4.9 lbs



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

***Vibration***

Drilling in metal - 2.2 m/s<sup>2</sup>

Uncertainty of measurement K - 1.5 m/s<sup>2</sup>

***Noise emission***

Sound pressure level - 76 dB(A)

Sound power level (LwA) - 87 dB(A)

Uncertainty of measurement K - 3 dB(A)