

18V BRUSHLESS LTX CLASS HAMMER DRILL - 602360850 BY METABO



SKU	Option	Part #	Price
5011708		602360850	\$389

Model	
Type	Hand Tools
SKU	5011708
Part Number	602360850
Barcode	4061792188174
Brand	Metabo
Packaging + Shipping	
Shipping Weight (Gross)	3.3 kg



Features

- Brushless hammer drill with maximum power for demanding applications
- Hammer drill function for drilling in masonry
- Selectable "impuls" mode for removal of stubborn screws and for spot-drilling on smooth surfaces
- Precision Stop: electronic torque control with increased precision for precise, delicate working
- Electronic safety shutdown: no kickback if the drill bit stops unexpectedly - for high user safety
- Integrated LED work light with afterglow function for optimal brightness in the work area
- With handy belt hook and bit case which can be fixed either on the right or left side
- Many brands, one battery pack system: This product can be combined with all 18V battery packs and chargers of the CAS brands: www.cordless-alliance-systems.com

Specifications

Characteristics

- Type of battery pack - Li-Power
- Battery voltage - 18 V
- Maximum torque, soft - 65 Nm / 575 ft. lbs
- Pulse torque - 65 Nm / 575 in-lbs
- Maximum torque, hard - 130 Nm / 1151 ft. lbs
- Adjustable torque - 1 - 20 Nm // 9 - 177 in-lbs
- Drill-Ø masonry - 16 mm / 5/8 "
- Drill Ø steel - 13 mm / 1/2 "
- Drill-Ø soft wood - 68 mm / 2.68 "
- No-load speed - 0 - 550 / 0 - 2000 rpm
- Maximum impact rate - 38000 bpm
- Chuck capacity - 1.5 - 13 mm // 1/16 - 1/2 "
- Collar diameter - 43 mm / 1 11/16 "
- Weight without battery pack - 1.8 / 4
- Weight with battery pack - 2.2 kg / 4.9 lbs

Vibration

- Drilling in metal - 2.6 m/s²
- Uncertainty of measurement K - 1.5 m/s²



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Impact drilling concrete - 16.5 m/s²

Uncertainty of measurement K - 1.7 m/s²

Noise emission

Sound pressure level - 92 dB(A)

Sound power level (LwA) - 103 dB(A)

Uncertainty of measurement K - 3 dB(A)