

### 23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

# 125MM 1500W ANGLE GRINDER WE 1500-125 RT (601241000) BY METABO





SKU	Option	Part #	Price
5011754		601241000	\$355

Model	
Туре	Angle Grinder
SKU	5011754
Part Number	601241000
Barcode	4007430297334
Brand	Metabo
Technical - Main	
Motor Power (Input)	2HP (1500W)
Motor Speed - No Load	11000 rpm
Packaging + Shipping	
Shipping Weight (Gross)	2.4 kg



#### **Features**

Powerful and robust angle grinder with ergonomic soft handle

for low-fatigue working, especially overhead Powerful motor with good overload capacity

Tacho Constamatic (TC) Full-wave Electronics: fast work progress by means of constant speed under load

Tool-free adjustable guard; twist-proof

Electronic safety shutdown: reduces kickback if the disc stops

unexpectedly - for high user safety

Electronic soft start for smooth start-up

Restart protection after power interruption

Auto-stop carbon brushes to protect the motor

The machine shown may differ in equipment and technical

details depending on the configuration.

Kindly pay attention to delivery scope and product

description.

 $\label{lem:conditional} \mbox{Accessories included only if listed in the delivery scope.}$ 

#### **Specifications**

Disc-Ø: 125 mm // 5 "
Rated input power: 1500 W
Output power: 900 W
No-load speed: 11000 rpm
Speed at rated load: 11000 rpm
Torque: 4.2 Nm / 37.2 ft. lbs
Spindle thread: M 14

Weight (without power cable): 2.4 kg / 5.3 lbs

Cable length: 4 m / 13 ft

Vibration:

Surface grinding: 9 m/s<sup>2</sup>

Uncertainty of measurement K: 1.5 m/s  $^{\rm 2}$  Grinding with sandpaper: 5.3 m/s $^{\rm 2}$  Uncertainty of measurement K: 1.5 m/s  $^{\rm 2}$ 

Noise emission:

Sound pressure level: 87 dB(A) Sound power level (LwA): 98 dB(A)



## 23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

Uncertainty of measurement K: 3 dB(A)

Includes: Guard Inner Support Flange Nut with two holes Side handle Flat-pin spanners