

## 250MM BENCH GRINDER, MULTI-TOOL PO484 ATTACHMENT ON TM400-250 - PO484-250 BY ITM



SKU	Option	Part #	Price
5041559		PO484-250	\$1270

Model	
Type	Bench Grinder
SKU	5041559
Part Number	PO484-250
Barcode	9328042031433
Brand	ITM
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg



### FEATURES

Combine the robust TM400-250 ITM 250mm Bench Grinder with one of Australia's leading belt grinding attachments PO484.

#### TM400-250

Powerful 900W Induction Motor.

25mm width grinding wheels

Cast iron body and base for long lasting performance.

Vibration absorbing pads on base for smoother running.

Capacitor Start-Run motor for maximum performance.

Heavy Duty tool rests for maximum user control.

Large eyes shield for increased user safety.

#### PO484

The Multitool is a renowned, Australian designed belt grinding attachment which can be used on most bench grinders. The technology replaces the grinding wheel and converts a traditional grinder into a sophisticated work station ideal for sanding, grinding, sharpening, shaping, polishing and refinishing.

**EFFICIENCY** - Superior performance and a user friendly, toolless belt change in under 5 seconds.

**VERSATILITY** - Grinding, sanding or polishing in 4 positions on rubber contact wheel, platen, disc or free strapping. The unit can also be swivelled vertically or any position in between.



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

ACCURATE TRACKING - The running position of the belt is simple to adjust and it stays there, allowing for finishing into sharp corners.

QUALITY CONSTRUCTION - Robust, maintenance free with sealed ball bearings, hardened and ground essential components and zinc plating.

3 YEAR WARRANTY - Against faulty materials and workmanship, even when used commercially.

**SPECIFICATIONS**

48" x 4" wide (1220 x 100mm) belt.

7" (178mm) diameter disc.

3 1/2" (89mm) diameter rubber contact wheel.