


## HOLEMAKER SPECIAL 80 MAGNETIC BASE DRILL, 240V, 3MT, CAP: 80MM DIA X 110MM DEPTH - HMSPECIAL80 BY ITM



SKU	Option	Part #	Price
5041677		HMSPECIAL80	\$5699

Model	
Type	Base Drill
SKU	5041677
Part Number	HMSPECIAL80
Barcode	9328042031358
Brand	Holemaker ITM
Technical - Main	
Mount	M14
Country of Origin	
Designed, Researched & Developed in	Japan
Workshop (Site) Info	
Electrical Connection	Australian AC 230V 50Hz
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg
Shipping Notes	This product is classified as 'Heavy / Oversized' and generally does not qualify for FREE SHIPPING.

### FEATURES

#### #3 MORSE TAPER, VERSATILE DRILLING & TAPPING MACHINE

The Holemaker Special 80 is a highly versatile European made machine for professional drilling and tapping applications, featuring the latest innovations in drilling machine technology. The machine's forward & reverse work modes with variable speed adjustment allows thread cutting up to M24 of through holes and blind holes.

#### Features

- New generation Italian made motor
- Intelligent speed control system maintains stable speed regardless of load changes
- Electronic Variable Speed Control
- Electronic clutch
- Overload and Overheat protection
- Tilt sensor stops the motor in cases of machines break away
- 360-degree visual monitoring system indicates current condition of the drill and gives safety and diagnostic information e.g. worn brushes
- Intuitive control panel at top of the drill
- Very light weight
- Supplied in a durable blow mould carry case with cutter guard & safety strap

#### SPECIFICATIONS



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

Capacity ( Diameter ): 80mm

Capacity ( Depth ): 110mm

Twist drill capacity: 25mm

Tap capacity: M24

#3 Morse Taper spindle

Input power: 1600 Watt Single Phase 240V

Motor Power: 1500 Watt

2 Speed variable gearbox (120-190 / 290-450rpm)

Lightweight, only 18kg

11000Nm Magnetic dead lift on 25mm steel plate

190mm Stroke

Height 554mm min / 744mm max