


## HOLEMAKER SPECIAL 140 MAGNETIC BASE DRILL, 240V, 4MT, CAP: 150MM DIA X 110MM DEPTH - HMSPECIAL140 BY ITM



SKU	Option	Part #	Price
5041679		HMSPECIAL140	\$7999

Model	
Type	Base Drill
SKU	5041679
Part Number	HMSPECIAL140
Barcode	9328042031228
Brand	Holemaker ITM
Technical - Main	
Mount	M14
Country of Origin	
Designed, Researched & Developed in	Japan
Workshop (Site) Info	
Electrical Connection	Australian AC 230V 50Hz
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg
Shipping Notes	This product is classified as 'Heavy / Oversized' and generally does not qualify for FREE SHIPPING.



### Features:

#4 MORSE TAPER HEAVY DUTY DRILLING & TAPPING MACHINE

The Holemaker Special 140 is a highly versatile European made machine for professional drilling and tapping applications, featuring the latest innovations in drilling machine technology. The machine's forward & reverse work modes with variable speed adjustment allows thread cutting up to M42 of through holes and M33 blind holes.

### Features

- New generation Italian made motor
- Intelligent speed control system maintains stable speed regardless of load changes
- Electronic Variable Speed Control
- Electronic clutch
- Overload and Overheat protection
- Tilt sensor stops the motor in cases of machines break away
- 360-degree visual monitoring system indicates current condition of the drill and gives safety and diagnostic information e.g. worn brushes
- Intuitive control panel at top of the drill
- Very light weight
- Supplied in a metal carry case with cutter guard & safety strap



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

**Specifications:**

Capacity ( Diameter ): 150mm

Capacity ( Depth ) : 110mm

Twist drill capacity: 47mm

Tap capacity: M42

#4 Morse Taper spindle

2150 Watt 240V motor

4 Speed variable gearbox (55-85 / 100-150 / 200-300 / 350-520rpm)

Lightweight, only 31kg

25000Nm Magnetic dead lift on 25mm steel plate

260mm Stroke

Height 634mm min / 894mm max