

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

2.25MM BRIGHT HSS JOBBER DRILL BIT 2007-2.25 BY BORDO



| in 2000 cm |
|--------------|
| |
| 121/22/22/28 |
| 24.053330 |
| 120727.642 |
| SP.Carmina |
| LACK SAL |
| |

| SKU Option Part # Price 56108 2007-2.25 \$2.6 | | | | |
|---|-------|--------|-----------|-------|
| SKU Option Part # Price | 56108 | | 2007-2.25 | \$2.6 |
| | SKU | Option | Part # | Price |

| Model | |
|-------------------------|---------------|
| SKU | 56108 |
| Part Number | 2007-2.25 |
| Barcode | 9326518000389 |
| Brand | Bordo |
| Packaging + Shipping | |
| Shipping Weight (Gross) | 0.0 kg |

BORDO METRIC QUICK SILVER M2 HSS JOBBER DRILLS

DIN338 118° Split Point (crankshaft point) Split point is self centering and reduces the need for end thrust. Friction at workpiece is reduced. 118º point angles are ideal for use in materials such as mild steel and cast iron. The 118º point creates easily controlled chips which are wide and thin. **DRILL BIT SURFACE TREATMENT** Bright Finish Jobber Drills have no surface treatment and are supplied in the as-ground condition. These tools are suitable for general purpose use, particularly for non-ferrous applications. Specifications: Spindle Speed Stainless Steel RPM: 1699 Spindle Speed Tool Steel RPM: 2548 Spindle Speed Cast Iron RPM: 3397 Spindle Speed Malleable Iron RPM: 3822 Spindle Speed Med. Carbon Steel RPM: 4247 Spindle Speed Free Cutting Steel RPM: 6087 Spindle Speed Aluminium/Brass RPM: 8635 Spindle Speed Wood/Plastic RPM: 12882 Feed per revolution mm: 0.07