



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

5/16" X 24 UNF BOTTOMING CHROME TAP - 4234-5/16B BY BORDO



SKU	Option	Part #	Price
56122		4234-5/16B	\$9.4

Model	
Type	Bottoming Tap
SKU	56122
Part Number	4234-5/16B
Barcode	9326518044383
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com



About this product:

5/16" x 24 UNF Bottoming Chrome Tap



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Chrome Alloy UNF Bottoming Hand Tap.

Used as thread chasers to clean an existing thread.

They can also be used to create a new female thread in non-ferrous metals and plastics.

Chrome alloy taps are not suitable for creating precision, safety or critical threads.

Unified National Fine thread form was introduced in 1948 as an attempt to standardise thread forms in the USA, Canada and the UK.

The thread profile of UNF is the same as for metric threads and is described in the JIS B0206 standard.

The thread is described by its major diameter and the number of threads per inch of length (TPI).

When used on external threads this series has greater tensile stress area than coarse threads of the same size.

Fine series threads will resist stripping out better than coarse threads in areas where the external and mating internal threads are subjected to loads equal to or greater than the capacity of the screw or bolt.

Fine threads are also used where the length of engagement is limited 1-1/4 or where wall thickness demands a fine pitch.

Bottoming Taps have a lead of two threads and are used to ensure minimum thread run-out when tapping to the bottom of a blind hole.

Bottoming Taps are typically preceded by the use of a Taper or Intermediate Tap.