



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

UNF INTERMEDIATE CHROME TAP BY BORDO



SKU	Option	Part #	Price
56131	Size: 1/2" x 20TPI	4234-1/2I	\$13.52
56128	Size: 1/4" x 28TPI	4234-1/4I	\$8.5
56129	Size: 3/8" x 24TPI	4234-3/8I	\$9.4
56130	Size: 7/16" x 20TPI	4234-7/16I	\$12.5

Model	
Type	Intermediate Tap
SKU	56131
Part Number	4232-1/2I
Barcode	9326518044222
Brand	Bordo
Packaging + Shipping	
Shipping Weight (Gross)	0.0 kg



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com



About this product:

Chrome Alloy UNF Intermediate Hand Tap.



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Used as thread chasers to clean an existing thread.

They can also be used to create a new female thread in non-ferrous metals and plastics.

Chrome alloy taps are not suitable for creating precision, safety or critical threads.

Unified National Fine thread form was introduced in 1948 as an attempt to standardise thread forms in the USA, Canada and the UK.

The thread profile of UNF is the same as for metric threads and is described in the JIS B0206 standard.

The thread is described by its major diameter and the number of threads per inch of length (TPI).

When used on external threads this series has greater tensile stress area than coarse threads of the same size.

Fine series threads will resist stripping out better than coarse threads in areas where the external and mating internal threads are subjected to loads equal to or greater than the capacity of the screw or bolt.

Fine threads are also used where the length of engagement is limited 1-1/4 or where wall thickness demands a fine pitch.

Intermediate Taps have a lead of four threads and are used in most general purpose applications to cut a thread true to a pre-drilled pilot hole.