

## 23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

## 1.5MM CARDED BRIGHT HSS JOBBER DRILL BIT 2PCE CLAM 2007-1.50S BY BORDO





DIN338 **118** ° **Split Point** (crankshaft point) Split point is self centering and reduces the need for end thrust. Friction at workpiece is reduced. 118  $^{\rm o}$  point angles are ideal for use in materials such as mild steel and cast iron. The 118  $^{\rm o}$  point creates easily controlled chips which are wide and thin.

**DRILL BIT SURFACE TREATMENT** Bright Finish Jobber Drills have no surface treatment and are supplied in the as-ground condition. These tools are suitable for general purpose use, particularly for non-ferrous applications. **Specifications:** 

Spindle Speed Stainless Steel RPM: 2548

Spindle Speed Tool Steel RPM: 3822 Spindle Speed Cast Iron RPM: 5096 Spindle Speed Malleable Iron RPM: 5733

Spindle Speed Med. Carbon Steel RPM: 6370 Spindle Speed Free Cutting Steel RPM: 9130 Spindle Speed Aluminium/Brass RPM: 12952 Spindle Speed Wood/Plastic RPM: 19322

Feed per revolution mm: 0.05



| SKU   | Option | Part #     | Price |
|-------|--------|------------|-------|
| 56132 |        | 2007-1.50S | \$5.3 |

| Model                   |               |
|-------------------------|---------------|
| Туре                    | Drill Bit     |
| SKU                     | 56132         |
| Part Number             | 2007-1.50S    |
| Barcode                 | 9326518035381 |
| Brand                   | Bordo         |
| Size                    | 1.5mm         |
| Technical - Main        |               |
| Flute Length            | 18mm          |
| Workshop (Site) Info    |               |
| Flute Length            | 18mm          |
| Packaging + Shipping    |               |
| Shipping Weight (Gross) | 1.48 kg       |
| Quantity Per Pack       | 2             |