

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

2.5MM CARDED BRIGHT HSS JOBBER DRILL BIT 2PCE CLAM 2007-2.50S BY BORDO



BORDO METRIC QUICK SILVER M2 HSS JOBBER DRILLS DIN338 118 ° Split Point (crankshaft point) Split point is self

centering and reduces the need for end thrust. Friction at workpiece is reduced. 118 ^o point angles are ideal for use in materials such as mild steel and cast iron. The 118 ° point creates easily controlled chips which are wide and thin. **DRILL BIT SURFACE TREATMENT** Bright Finish Jobber Drills have no surface treatment and are supplied in the as-ground condition. These tools are suitable for general purpose use, particularly for non-ferrous applications. Specifications: Spindle Speed Stainless Steel RPM: 1529 Spindle Speed Tool Steel RPM: 2293 Spindle Speed Cast Iron RPM: 3058 Spindle Speed Malleable Iron RPM: 3440 Spindle Speed Med. Carbon Steel RPM: 3822 Spindle Speed Free Cutting Steel RPM: 5478 Spindle Speed Aluminium/Brass RPM: 7771 Spindle Speed Wood/Plastic RPM: 11593 Feed per revolution mm: 0.07



SKU	Option	Part #		Price
56134		2007-2.505		\$5.5
Model				
Туре			Drill Bit	
SKU			56134	
Part Number			2007-2.505	
Barcode			9326518035404	
Brand			Bordo	
Size			2.5mm	
Technical - Main				
Flute Length			30mm	
Workshop (Site) Info				
Flute Length			30mm	
Packaging + Shipping				
Shipping Weight (Gross)			1.48 kg	
Quantity Per Pack			2	