



HIGH GLOSSY GOLD ALUMINIUM EDGING U/G PER METRE M6 BY GILDO PROFILATI



SKU	Option	Part #	Price
8000038	Size: 22mm, Quantity: 100m	M6	\$3
8000038-25	Size: 22mm, Quantity: 25m (Cut of Full Roll - Cutting Surcharge Applies)	M6	\$75
8000055	Size: 38mm, Quantity: 100m	M6	\$6
8000055-1	Size: 38mm, Quantity: 1m		\$
8000055-25	Size: 38mm, Quantity: 25m (Cut of Full Roll - Cutting Surcharge Applies)	M6	\$100

Model	
Type	Edgebanding Tape - Aluminium
SKU	8000038-25
Part Number	M6
Brand	Gildo Profilati
Country of Origin	
Manufactured in	Italy
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg



Gildo Profilati's edgebanding tape is a top quality, highly prestigious product offering a unique and exclusive look. Provided with a water based primer overleaf, they are applied with the aid of traditional hot working edgebanders. They are protected by a protective film to then be removed after application, once the object is finished. Gildo Profilati's edgebanding tape are non-toxic and fire-proof.

Application tips and technical information

It is recommended that an appropriate adjustment of the edgebander by a skilled operator

We strongly recommend the use of sharp blades

Gently and slowly remove the protective film

Features

Stocking temperature: 15-20 degrees C, humidity 55-65%

In case of cold stocking retrieve the edge bandings 12 hours at least before



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com



GILDO PROFILATI

processing until they reach the suggested

stocking temperature

Workplace temperature: 15-25 C°

HOT MELT Temperature: 200/210 ° C

HOT MELT type: HENKEL DORUS KS 351

Edgebander type: BIESSE STREAM B1 and
similar

Application speed: 18/25 metres / minute