



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

## 315MM (12.5") SWING X 510MM (20") BETWEEN CENTRES VARIABLE SPEED MIDI LATHE 70-220VSR BY RIKON



315mm x 510mm Variable Speed Midi Lathe #70-220VSR is basically a scaled-down, portable version of larger, free-standing lathes using tools rests with 25mm diameter posts. Designed and constructed heavier than the mini lathe for added stability, this newly designed machine has features requested by professionals - a more powerful 1HP motor, electronic variable speed controls, a wider range of operating speeds, digital RPM readout, forward/reverse drive, index settings, and larger diameter and spindle length turning capacity.

### Features

- 315mm (12.5") Swing / 510mm (20") Between Centres
- 24 Position Index Head
- Easy Access Speed Change
- Nylon Face Plate Washer
- Self Ejecting Tail Stock
- Ability To Add Multiple Extensions
- 1HP motor delivers all the power you need for turning spindles to large bowls or platters
- Big turning capacity of 12-1/2" diameter swing and 20" between centres
- 24 Position Index head allows accurate pattern or design work on projects
- Electronic variable speeds 250-3850RPM with LED display and forward/reverse functions

SKU	Option	Part #	Price
8000725		70-220VSR	\$1399

Model	
Type	Woodturning Lathe
SKU	8000725
Part Number	70-220VSR
Barcode	08000725
Brand	Rikon
Technical - Main	
Power Source	230-240V 50Hz (Single Phase)
Motor Power (Output)	1HP (0.74kW)
Dimensions	
Product Weight (Net Weight)	56 kg
Country of Origin	
Manufactured in	China
Features	
Variable Speed	✓
Standard Inclusions	315mm (12.5") Swing x 510mm (20") Between Centres Variable Speed MIDI Lathe 70-220VSR by Rikon
Warranty	
Warranty	5 Years
Packaging + Shipping	
Shipping Length	1000 mm
Shipping Width	550 mm
Shipping Height	350 mm
Shipping Weight (Gross)	76.0 kg
Requires a Skid to Ship	✓
Requires a Forklift / Tail Lift to Unload	✓
Shipping Notes	This product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to safely transport via road.