

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com



315MM (12") 3HP 1.6M SLIDING TABLE SAW 240V TS315B BY WOODFAST *SPECIAL ORDER*





315mm (12") 3HP 1.6m Sliding Table Saw 240V TS315B by Woodfast. It boasts a powerful motor and a long sliding table for precise, fast cuts. Enjoy the improved accuracy and speed —perfect for all types of woodworking projects.

Not every workshop needs a large panel saw dominating the workspace, but a compact, fully featured saws is a tempting alternative. The TS315B is just that, having a robustly constructed chassis in a heavy gauge steel and generous grey cast iron table with real panel saw trunnion, that gives stability and vibration free running.

Features

Cast iron saw unit provides extra support and stability for reduced vibration

Large sectional profile cross cutting fence with reversible fence stops

Solid cast iron rip fence with aluminium profile mounted to 150mm bar, for accurate reliable ripping

Ball bearing sliding along tempered and ground prismatic guides guarantees smooth and precise sliding and cutting.

Specification

Scoring Motor Power: 1HP

Scoring Blade Speed: 8000RPM Major Table Size: 800mm (530+820mm)

Sliding Table Size: 1200 x 312mm

Sliding Table Cutting Capacity / Rip (Blade to Rip Fence): 1250mm

SKU	Option	Part #	Price	
8000849		TS315B	\$7899	
Model				
Туре		Panel Sa	Panel Saw	
SKU	8000849	8000849		
Part Number		TS315B	TS315B	
Brand		Woodfas	Woodfast	
Size	315mm (315mm (12")		
Technical - Main				
Power Source	240V 50I	240V 50Hz Single Phase		
Motor Power (Input)	3HP / 22	3HP / 2200W		
Cutting Capacity - H	eight	80 mm	80 mm	
Table Size		800 (530	800 (530 +820)mm	
Technical - Saw				
Sliding Table (Cross	Cut) Size	1200mm	1200mm x 312mm	
Rip Capacity	1250 mn	1250 mm		
Blade (Main) - Bore S	Size (mm)	30mm	30mm	
Blade (Main) - Diame	eter (Max.)	315 mm	315 mm	
Blade (Main) - Speed	ł	4000RPM	4000RPM	
Blade (Scoring) - Dia	meter (Max.)	120 mm	120 mm	
Blade (Scoring) - Bore Size		20 mm	20 mm	
Blade (Scoring) - Speed		8000RPM	8000RPM	
Blade Tilt		0° to 45	0° to 45°	
Dimensions				
Product Weight (Net	Weight)	425 kg	425 kg	
Country of Origin				
Manufactured in		China	China	
Safety				
Emergency Stop Swi	itch	✓		
Blade Guard		✓	✓	
Dust Port		1 x 100m	nm, 1 x 80mm	
Workshop (Site) Ir	ıfo			
Electrical Connection	า	15Amp P	15Amp Plug & Lead	
Workshop Requirem	ents	Dust Ext	Dust Extraction	
Warranty				
Warranty		1 Year	1 Year	
Use			Not intended or designed for commercial use.	
Packaging + Shipp	oing			
Shipping Weight (Gr		495.0 kg	495.0 kg	

WWW.BEYONDTOOLS.COM - © COPYRIGHT 2024 BEYOND TOOLS - VERSION: 20240509



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm



Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

Maximum Cut Depth: 95mm at 90° / 67mm at 45° **Optional Accessories** Angled Cutting Device 100mm Dust Hose Hose Clamps + fittings etc Dust Extractor FM Series Dust Collector

Packaging	Wooden Box / Crate with Skid	
Packaging Box Qty	2	
Carton 1 (L X W X H x KG)	1310mm x 990mm x 1085mm	
Carton 2 (L X W X H x KG)	2000mm x 430mm x 210mm	
Requires a Forklift / Tail Lift to Unload	✓	
Shipping Notes	This product is classified as 'Heavy / Oversized' and generally does not qualify for FREE SHIPPING.	

WWW.BEYONDTOOLS.COM - © COPYRIGHT 2024 BEYOND TOOLS - VERSION: 20240509