
woodfastmachinery.com.au

WOODFAST

315MM (12") 3HP 2.6M SLIDING PANEL SAW 240V PS315B BY WOODFAST *SPECIAL ORDER*













315mm (12") 3HP 1.6m Sliding Table Saw 240V TS315B by Woodfast. It boasts a powerful motor and a long sliding table for precise, fast cuts. Enjoy the improved accuracy and speed —perfect for all types of woodworking projects.

Not every workshop needs a large panel saw dominating the workspace, but a compact, fully featured saws is a tempting alternative. The TS315B is just that, having a robustly constructed chassis in a heavy gauge steel and generous grey cast iron table with real panel saw trunnion, that gives stability and vibration free running.

Features

Cast iron saw unit provides extra support and stability for reduced vibration

Large sectional profile cross cutting fence with reversible fence stops

Solid cast iron rip fence with aluminium profile mounted to 150mm bar, for accurate reliable ripping

Ball bearing sliding along tempered and ground prismatic guides guarantees smooth and precise sliding and cutting.

Specifications

Main Motor Power: 3HP
Main Blade Speed: 4000RPM
Scoring Motor Power: 1HP
Scoring Blade Speed: 8000RPM

Blade Tilt: 0-45°

Major Table Size: 800mm (530+820mm) Sliding Table Size: 1200 x 312mm

Sliding Table Cutting Capacity / Rip (Blade to Rip Fence):

1250mm

Maximum Cut Depth: 95mm at 90° / 67mm at 45°

Optional Accessories

Model Type Panel Saw SKU 8000851 Part Number P53158-240V Brand Woodfast Size 315mm (12") Technical - Main Power Source 240V 50Hz Single Phase Motor Power (Input) 3HP / 2200W Cutting Capacity - Height 80 mm Table Size 2600 x 375mm Technical - Saw Technical - Saw Sliding Table (Cross Cut) Size 2600mm x 375mm Rip Capacity 1250 mm Blade (Main) - Bore Size (mm) 30mm Blade (Main) - Bore Size (mm) 30mm Blade (Scoring) - Diameter (Max.) 120 mm Blade (Scoring) - Bore Size 20 mm Blade (Scoring) - Speed 8000RPM Blade Tilt 0Ű to 45Ű Dimensions Product Weight (Net Weight) 520 kg Safety Emergency Stop Switch ✓ Blade Guard ✓ ✓ Dust Pure Suppling 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection<		
SKU 8000851 Part Number PS315B-240V Brand Woodfast Size 315mm (12") Technical - Main Power Source 240V 50Hz Single Phase Motor Power (Input) 3HP / 2200W Cutting Capacitry - Height 80 mm Table Size 2600 x 375mm Technical - Saw Sliding Table (Cross Cut) Size 2600mm x 375mm Rip Capacity 1250 mm Blade (Main) - Bore Size (mm) 30mm Blade (Main) - Diameter (Max.) 315 mm Blade (Main) - Speed 4000RPM Blade (Scoring) - Diameter (Max.) 120 mm Blade (Scoring) - Bore Size 20 mm Blade (Scoring) - Speed 8000RPM Blade Scoring) - Speed 8000RPM Blade Tilt 0Ű to 45Ű Dimensions Product Weight (Net Weight) 520 kg Safety Emergency Stop Switch ✓ Blade Guard ✓ Dust Port 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection 15Amp Plug & Lead Workshop Requirements Dust Extraction Warranty 1 Year Use Not intended or designed for commercial use. Packaging + Shipping Shipping Weight (Gross) 640.0 kg Packaging Box Qty 2 Carton 1 (L X W X H x KG) 2960mm x 480mm x 210mm x 1150mm x 1150mm x 1150mm x 1150mm x 1150mm x 120mm x 2000mm x 1150mm x 1150mm x 1150mm x 120mm x 2000mm x 1150mm x 1150mm x 1150mm x 120mm x 2000mm x 480mm x 210mm x 2000mm	Model	
Part Number Prover Source Motor Power (Input) Technical - Main Power Source Motor Power (Input) Table Size Technical - Saw Sliding Table (Cross Cut) Size Rip Capacity Blade (Main) - Bore Size (mm) Blade (Main) - Diameter (Max.) Blade (Main) - Speed Blade (Scoring) - Diameter (Max.) Blade (Scoring) - Bore Size Blade (Scoring) - Speed Blade (Scoring) - Speed Blade (Scoring) - Speed Blade (Storing) - Speed Blade (Storing) - Speed Blade (Storing) - Speed Blade (Scoring) - Speed Blade (Storing) - S	Туре	Panel Saw
Brand Woodfast Size 315mm (12") Technical - Main Power Source 240V 50Hz Single Phase Motor Power (Input) 3HP / 2200W Cutting Capacity - Height 80 mm Table Size 2600 x 375mm Technical - Saw Sliding Table (Cross Cut) Size 2600mm x 375mm Rip Capacity 1250 mm Blade (Main) - Bore Size (mm) 30mm Blade (Main) - Diameter (Max.) 315 mm Blade (Main) - Speed 4000RPM Blade (Scoring) - Diameter (Max.) 120 mm Blade (Scoring) - Bore Size 20 mm Blade (Scoring) - Speed 8000RPM Blade (Scoring) - Speed 8000RPM Blade Tilt 0Ű to 45Ű Dimensions Product Weight (Net Weight) 520 kg Safety Emergency Stop Switch ✔ Blade Guard ✔ Dust Port 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection 15Amp Plug & Lead Workshop Requirements Dust Extraction Warranty Warranty 1 Year Use Not intended or designed for commercial use. Packaging + Shipping Shipping Weight (Gross) 640.0 kg Packaging Box Qty 2 Carton 1 (L X W X H x KG) 2000mm x 480mm x 210mm Requires a Forklift / Tail Lift to Unload ✔	SKU	8000851
Size 315mm (12") Technical - Main Power Source 240V 50Hz Single Phase Motor Power (Input) 3HP / 2200W Cutting Capacity - Height 80 mm Table Size 2600 x 375mm Technical - Saw Sliding Table (Cross Cut) Size 2600mm x 375mm Rip Capacity 1250 mm Blade (Main) - Bore Size (mm) 30mm Blade (Main) - Diameter (Max.) 315 mm Blade (Main) - Speed 4000RPM Blade (Scoring) - Diameter (Max.) 120 mm Blade (Scoring) - Bore Size 20 mm Blade (Scoring) - Bore Size 20 mm Blade (Scoring) - Speed 8000RPM Blade (Scoring) - Speed 8000RPM Blade Tilt 0ð to 45ð Dimensions Product Weight (Net Weight) 520 kg Safety Emergency Stop Switch ✓ Blade Guard ✓ Dust Port 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection 15Amp Plug & Lead Workshop Requirements Dust Extraction Warranty Use Not intended or designed for commercial use. Packaging + Shipping Shipping Weight (Gross) 640.0 kg Packaging Box Qty 2 Carton 1 (L X W X H x KG) 2000mm x 480mm x 210mm Requires a Forklift / Tail Lift to Unload ✓	Part Number	PS315B-240V
Technical - Main Power Source 240V 50Hz Single Phase Motor Power (Input) 3HP / 2200W Cutting Capacity - Height 80 mm Table Size 2600 x 375mm Technical - Saw Sliding Table (Cross Cut) Size Rip Capacity Blade (Main) - Bore Size (mm) Blade (Main) - Diameter (Max.) Blade (Main) - Speed 4000RPM Blade (Scoring) - Diameter (Max.) 120 mm Blade (Scoring) - Bore Size 20 mm Blade (Scoring) - Speed 8000RPM Blade (Scoring) - Speed 8000RPM Blade (Scoring) - Speed Blade Tilt 0Ű to 45Ű Dimensions Product Weight (Net Weight) 520 kg Safety Emergency Stop Switch V Emergency Stop Switch V Electrical Connection 15Amp Plug & Lead Workshop (Site) Info Electrical Connection 15Amp Plug & Lead Workshop Requirements Dust Extraction Warranty Use Packaging + Shipping Shipping Weight (Gross) 640.0 kg Packaging Packaging Box Qty 2 Carton 1 (L X W X H x KG) 2960mm x 480mm x 210mm Requires a Forklift / Tail Lift to Unload ✓	Brand	Woodfast
Power Source Motor Power (Input) Cutting Capacity - Height Table Size Power (Source) Sliding Table (Cross Cut) Size Rip Capacity Blade (Main) - Bore Size (mm) Blade (Main) - Speed Blade (Scoring) - Diameter (Max.) Blade (Scoring) - Bore Size Blade (Scoring) - Speed Blade Scoring) - Speed Blade Scoring - Speed Blade Scoring - Speed Blade Scoring - Speed Blade Scoring - Speed Blade Filt Dimensions Product Weight (Net Weight) Safety Emergency Stop Switch Blade Guard Dust Port 1 x 120 mm Workshop (Site) Info Electrical Connection Workshop Requirements Dust Extraction Warranty Use Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Capacity Somm Somm 30mm 4000RPM 4000RPM 8000RPM 900RPM	Size	315mm (12")
Motor Power (Input) Cutting Capacity - Height Table Size 2600 x 375mm Technical - Saw Sliding Table (Cross Cut) Size Rip Capacity Blade (Main) - Bore Size (mm) Blade (Main) - Diameter (Max.) Blade (Scoring) - Diameter (Max.) Blade (Scoring) - Bore Size Blade (Scoring) - Speed Blade Tilt 0Ű to 45Ű Dimensions Product Weight (Net Weight) 520 kg Safety Emergency Stop Switch Blade Guard Dust Port 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection Workshop Requirements Dust Extraction Warranty Use Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Capiculary 2600mm x 480mm x 210mm Requires a Forklift / Tail Lift to Unload	Technical - Main	
Cutting Capacity - Height Table Size 7echnical - Saw Sliding Table (Cross Cut) Size Rip Capacity Blade (Main) - Bore Size (mm) Blade (Main) - Diameter (Max.) Blade (Scoring) - Diameter (Max.) Blade (Scoring) - Speed Blade (Scoring) - Speed Blade (Scoring) - Speed Blade (Scoring) - Speed Blade Tilt Dimensions Product Weight (Net Weight) Safety Emergency Stop Switch Blade Guard Workshop (Site) Info Electrical Connection Workshop Requirements Warranty Use Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload ▼ 2600mm x 375mm 26000mm x 375mm 300mm 300mm 315 mm 300mm 315 mm 300mm 300mm 315 mm 300mm 315 mm 3000mp 4000RPM 3000RPM 315 mm 31	Power Source	240V 50Hz Single Phase
Table Size Technical - Saw Sliding Table (Cross Cut) Size Rip Capacity Blade (Main) - Bore Size (mm) Blade (Main) - Diameter (Max.) Blade (Main) - Speed 4000RPM Blade (Scoring) - Diameter (Max.) Blade (Scoring) - Bore Size Blade (Scoring) - Speed 8000RPM Blade (Scoring) - Speed Blade (Scoring) - Speed Blade Tilt 0° to 45° Dimensions Product Weight (Net Weight) Safety Emergency Stop Switch Blade Guard Vorkshop (Site) Info Electrical Connection Warranty Warranty Use Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload Vacon 2 (L X W X H x KG) 2600mm x 375mm 300mm 300mm 315 mm 300mm 315 mm 300mm 315 mm 300mm 315 mm 4000RPM 315 mm 4000R	Motor Power (Input)	3HP / 2200W
Technical - Saw Sliding Table (Cross Cut) Size Rip Capacity Blade (Main) - Bore Size (mm) Blade (Main) - Diameter (Max.) Blade (Main) - Speed 4000RPM Blade (Scoring) - Diameter (Max.) Blade (Scoring) - Bore Size 20 mm Blade (Scoring) - Speed 8000RPM Blade (Scoring) - Speed 8000RPM Blade Tilt 0° to 45° Dimensions Product Weight (Net Weight) 520 kg Safety Emergency Stop Switch Blade Guard Dust Port 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection 15Amp Plug & Lead Workshop Requirements Dust Extraction Warranty Use Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload ✓ 2600mm x 480mm x 210mm Requires a Forklift / Tail Lift to Unload	Cutting Capacity - Height	80 mm
Sliding Table (Cross Cut) Size Rip Capacity Blade (Main) - Bore Size (mm) Blade (Main) - Diameter (Max.) Blade (Main) - Speed Blade (Scoring) - Diameter (Max.) Blade (Scoring) - Diameter (Max.) Blade (Scoring) - Bore Size Blade (Scoring) - Speed Blade (Scoring) - Speed Blade (Scoring) - Speed Blade (Scoring) - Speed Blade Tilt O° to 45° Dimensions Product Weight (Net Weight) Safety Emergency Stop Switch Blade Guard Dust Port 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection 15Amp Plug & Lead Workshop Requirements Dust Extraction Warranty Use Not intended or designed for commercial use. Packaging + Shipping Shipping Weight (Gross) Packaging Wooden Box / Crate with Skid Packaging Box Qty 2 Carton 1 (L X W X H x KG) 2960mm x 480mm x 210mm Requires a Forklift / Tail Lift to Unload	Table Size	2600 x 375mm
Rip Capacity Blade (Main) - Bore Size (mm) Blade (Main) - Diameter (Max.) Blade (Main) - Speed 4000RPM Blade (Scoring) - Diameter (Max.) Blade (Scoring) - Bore Size 20 mm Blade (Scoring) - Speed 8000RPM Blade (Scoring) - Speed 8000RPM Blade Tilt 0Ű to 45Ű Dimensions Product Weight (Net Weight) 520 kg Safety Emergency Stop Switch Blade Guard Unst Port 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection 15Amp Plug & Lead Workshop Requirements Dust Extraction Warranty Use Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload Feduires a Forklift / Tail Lift to Unload ▼ 4000RPM 315 mm 30mm 30mm 30mm 30mm 315 mm 4000RPM 4000RPM Balde (Main) - Diameter (Max.) 120 mm 8000RPM 8000RPM 8000RPM 8000RPM 8000RPM 8000RPM 8000RPM 8000RPM	Technical - Saw	
Blade (Main) - Bore Size (mm) Blade (Main) - Diameter (Max.) Blade (Main) - Diameter (Max.) Blade (Main) - Speed 4000RPM Blade (Scoring) - Diameter (Max.) Blade (Scoring) - Bore Size 20 mm Blade (Scoring) - Speed 8000RPM Blade Tilt 0° to 45° Dimensions Product Weight (Net Weight) 520 kg Safety Emergency Stop Switch Blade Guard ✓ Dust Port 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection 15Amp Plug & Lead Workshop Requirements Dust Extraction Warranty Use Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload ▼ 4000RPM 120 mm 30mm 315 mm 315 mm 4000RPM 120 mm 120 mm 120 mm 120 mm 120 mm 4000RPM 120 mm 120 mm 120 mm 120 mm 4000RPM 120 mm 120 mm 120 mm 120 mm 4000RPM 120 mm	Sliding Table (Cross Cut) Size	2600mm x 375mm
Blade (Main) - Diameter (Max.) Blade (Main) - Speed 4000RPM Blade (Scoring) - Diameter (Max.) Blade (Scoring) - Bore Size 20 mm Blade (Scoring) - Speed 8000RPM Blade (Scoring) - Speed 8000RPM Blade Tilt 0Ű to 45Ű Dimensions Product Weight (Net Weight) 520 kg Safety Emergency Stop Switch Blade Guard □ ust Port 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection 15Amp Plug & Lead Workshop Requirements Dust Extraction Warranty Warranty Use Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload ▼ 2000mm x 480mm x 210mm Requires a Forklift / Tail Lift to Unload	Rip Capacity	1250 mm
Blade (Main) - Speed Blade (Scoring) - Diameter (Max.) Blade (Scoring) - Bore Size Blade (Scoring) - Speed Blade (Scoring) - Speed Blade (Scoring) - Speed Blade Tilt O° to 45° Dimensions Product Weight (Net Weight) Safety Emergency Stop Switch Blade Guard Dust Port 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection 15Amp Plug & Lead Workshop Requirements Dust Extraction Warranty Warranty Use Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload ### Wooden Box / Crate with Skid 2960mm x 480mm x 210mm Requires a Forklift / Tail Lift to Unload	Blade (Main) - Bore Size (mm)	30mm
Blade (Scoring) - Diameter (Max.) Blade (Scoring) - Bore Size Blade (Scoring) - Speed Blade (Scoring) - Speed Blade Tilt Dimensions Product Weight (Net Weight) Safety Emergency Stop Switch Blade Guard Dust Port Dust Port Workshop (Site) Info Electrical Connection Workshop Requirements Dust Extraction Warranty Warranty Use Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload Packaging Row Mooden Box / Carton medical use. Pach Mooden Box / Carton medical use. Packaging x 480mm x 210mm Requires a Forklift / Tail Lift to Unload	Blade (Main) - Diameter (Max.)	315 mm
Blade (Scoring) - Bore Size Blade (Scoring) - Speed Blade Tilt Oâ° to 45â° Dimensions Product Weight (Net Weight) Safety Emergency Stop Switch Blade Guard Dust Port 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection Workshop Requirements Dust Extraction Warranty Warranty Use Not intended or designed for commercial use. Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload Policy in 45â° 8000RPM 8000RPM 8000RPM 8000RPM 8000RPM 8000RPM 920 kg 8000RPM 8000RPM 920 kg 8000RPM 8000RPM 940 kg 8000RPM 920 mm 940 kg 940 Not intended or designed for commercial use. 940 Vooden Box / Crate with Skid 940 Square 1150mm x 1150mm x 1150mm 940 Square 1150mm x 1150mm x 1150mm 940 Square 1150mm x 1150mm 940 Square 1150mm x 1150mm 940 Square 1150mm x 1150mm x 1150mm x 1150mm 940 Square 1150mm x 1150mm x 1150mm x 1150mm 940 Square 1150mm x 1150mm x 1150mm x 1150mm 940 Square 1150mm x 1150mm x 1150mm	Blade (Main) - Speed	4000RPM
Blade (Scoring) - Speed Blade Tilt O° to 45° Dimensions Product Weight (Net Weight) Safety Emergency Stop Switch Blade Guard Dust Port Vorkshop (Site) Info Electrical Connection Workshop Requirements Warranty Warranty Use Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload 8200 RM 8000RPM 1 520 kg 800mm 1 x 120mm, 1 x 80mm 1 x 120mm, 1 x 80mm 1 Year 1 Year Not intended or designed for commercial use. 8000RPM 8000RPM 1 x 120 kg 8000RPM	Blade (Scoring) - Diameter (Max.)	120 mm
Blade Tilt Dimensions Product Weight (Net Weight) Safety Emergency Stop Switch Blade Guard Dust Port 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection 15Amp Plug & Lead Workshop Requirements Dust Extraction Warranty Warranty Use Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload P 520 kg 1 4 4 5 6 6 7 6 7 6 7 6 7 6 7 6 7 6 7 6 7 6 7	Blade (Scoring) - Bore Size	20 mm
DimensionsProduct Weight (Net Weight)520 kgSafety✓Emergency Stop Switch✓Blade Guard✓Dust Port1 x 120mm, 1 x 80mmWorkshop (Site) InfoI5Amp Plug & LeadElectrical Connection15Amp Plug & LeadWorkshop RequirementsDust ExtractionWarranty1 YearUseNot intended or designed for commercial use.Packaging + ShippingNoden Box / Crate with SkidPackagingWooden Box / Crate with SkidPackaging Box Qty2Carton 1 (L X W X H x KG)2000mm x 1150mm x 1150mmCarton 2 (L X W X H x KG)2960mm x 480mm x 210mmRequires a Forklift / Tail Lift to Unload✓	Blade (Scoring) - Speed	8000RPM
Product Weight (Net Weight) Safety Emergency Stop Switch Blade Guard Dust Port Vorkshop (Site) Info Electrical Connection Workshop Requirements Dust Extraction Warranty Use Not intended or designed for commercial use. Packaging + Shipping Shipping Weight (Gross) Packaging Packaging Wooden Box / Crate with Skid Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload	Blade Tilt	0° to 45°
Emergency Stop Switch Blade Guard Dust Port 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection 15Amp Plug & Lead Workshop Requirements Dust Extraction Warranty Use Not intended or designed for commercial use. Packaging + Shipping Shipping Weight (Gross) Packaging Packaging Wooden Box / Crate with Skid Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload	Dimensions	
Emergency Stop Switch Blade Guard Dust Port 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection Workshop Requirements Dust Extraction Warranty Warranty 1 Year Use Not intended or designed for commercial use. Packaging + Shipping Shipping Weight (Gross) Packaging Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload	Product Weight (Net Weight)	520 kg
Blade Guard Dust Port 1 x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection 15Amp Plug & Lead Workshop Requirements Dust Extraction Warranty Warranty 1 Year Not intended or designed for commercial use. Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload	Safety	
Dust Port I x 120mm, 1 x 80mm Workshop (Site) Info Electrical Connection Boust Extraction Warranty Warranty Use Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload I SAmp Plug & Lead Dust Extraction Not intended or designed for commercial use. A voucher Box / Crate with Skid 2 2000mm x 1150mm x 1150mm 2 960mm x 480mm x 210mm	Emergency Stop Switch	✓
Workshop (Site) Info Electrical Connection 15Amp Plug & Lead Workshop Requirements Dust Extraction Warranty 1 Year Use Not intended or designed for commercial use. Packaging + Shipping Shipping Weight (Gross) 640.0 kg Packaging Wooden Box / Crate with Skid Packaging Box Qty 2 Carton 1 (L X W X H x KG) 2000mm x 1150mm x 1150mm Carton 2 (L X W X H x KG) 2960mm x 480mm x 210mm Requires a Forklift / Tail Lift to Unload	Blade Guard	✓
Electrical Connection Workshop Requirements Dust Extraction Warranty Use 1 Year Not intended or designed for commercial use. Packaging + Shipping Shipping Weight (Gross) Packaging Packaging Wooden Box / Crate with Skid Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload	Dust Port	1 x 120mm, 1 x 80mm
Workshop Requirements Warranty Use Packaging + Shipping Shipping Weight (Gross) Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload Dust Extraction Dust Extraction Dust Extraction A Wooden Not intended or designed for commercial use. Not intended or designed for commercial use. Packaging House Wooden Box / Crate with Skid 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Workshop (Site) Info	
Warranty Use 1 Year Not intended or designed for commercial use. Packaging + Shipping Shipping Weight (Gross) Packaging Packaging Wooden Box / Crate with Skid Packaging Box Qty 2 Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload	Electrical Connection	15Amp Plug & Lead
Warranty Use Not intended or designed for commercial use. Packaging + Shipping Shipping Weight (Gross) Packaging Wooden Box / Crate with Skid Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload 1 Year Not intended or designed for commercial use. 240.0 kg Wooden Box / Crate with Skid 2 2 2 2000mm x 1150mm x 1150mm	Workshop Requirements	Dust Extraction
Use Not intended or designed for commercial use. Packaging + Shipping Shipping Weight (Gross) 640.0 kg Packaging Wooden Box / Crate with Skid Packaging Box Qty 2 Carton 1 (L X W X H x KG) 2000mm x 1150mm x 1150mm Carton 2 (L X W X H x KG) 2960mm x 480mm x 210mm Requires a Forklift / Tail Lift to Unload	Warranty	
commercial use. Packaging + Shipping Shipping Weight (Gross) 640.0 kg Packaging Wooden Box / Crate with Skid Packaging Box Qty 2 Carton 1 (L X W X H x KG) 2000mm x 1150mm x 1150mm Carton 2 (L X W X H x KG) 2960mm x 480mm x 210mm Requires a Forklift / Tail Lift to Unload	Warranty	1 Year
Shipping Weight (Gross) Packaging Wooden Box / Crate with Skid Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload 640.0 kg Wooden Box / Crate with Skid 2 2 2 2 2 2 2 2 2 2 2 2 2	Use	
Shipping Weight (Gross) Packaging Wooden Box / Crate with Skid Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload 640.0 kg Wooden Box / Crate with Skid 2 2 2 2 2 2 2 2 2 2 2 2 2	Packaging + Shipping	
Packaging Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload Wooden Box / Crate with Skid 2 2000mm x 1150mm x 1150mm x 1150mm 2960mm x 480mm x 210mm		640.0 kg
Packaging Box Qty Carton 1 (L X W X H x KG) Carton 2 (L X W X H x KG) Requires a Forklift / Tail Lift to Unload 2 2 2000mm x 1150mm x 1150mm x 1150mm 2960mm x 480mm x 210mm	Packaging	Wooden Box / Crate with Skid
Carton 1 (L X W X H x KG) 2000mm x 1150mm x 1150mm Carton 2 (L X W X H x KG) 2960mm x 480mm x 210mm Requires a Forklift / Tail Lift to Unload ✓		2
Carton 2 (L X W X H x KG) 2960mm x 480mm x 210mm Requires a Forklift / Tail Lift to Unload ✓		2000mm x 1150mm x 1150mm
Requires a Forklift / Tail Lift to Unload	,	
14		
	·	

woodfastmachinery.com.au

WOODFAST®

Angled Cutting Device 100mm Dust Hose Hose Clamps + fittings etc Dust Extractor FM Series Dust Collector 'Heavy / Oversized' and generally does not qualify for FREE SHIPPING.