

23 Exhibition Drive, Malaga Western Australia Monday - Friday 7am-5pm + Sat 8am-4pm



Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

SPECIAL ORDER 500MM (20") INDUSTRIAL BANDSAW OPAL TC500 BY TOUGHCUT





Features

305mm Re-Saw Capacity Dual 4" Dust Ports Double Bearing Blade Guide System Thickened Large Cast Iron Table with T Slot Design Fully Enclosed thickened Steel Body Quick Release Blade Tension Hinged Blade Guard with Sight Window Rack and Pinion Saw Blade Guide



SKU	Option	Part #		Price	
8000907	907 OPAL TC500		0	\$4799	
Model					
Туре			Bandsaw		
SKU			8000907		
Series			Opal		
Part Number			OPAL TC500		
Brand			ToughCut		
Size			500mm (20â()		
Technical - Mai	n				
Power Source			415V 50Hz Three Phase		
Motor Power (Input)			4HP / 3000W		
Bandwheel			500mm		
Bandwheel Diameter			3962 mm		
Blade Length			3962 mm		
Blade Width			6-30mm		
Cutting Capacity - Height			335 mm		
Throat Capacity			480 mm		
Table Size			633mm x 485mm		
Technical - Saw	I				
Blade (Main) - Speed			1500m / Min.		
Dimensions					
Product Length			1201 mm		
Product Width			889 mm		
Product Height			2017 mm		
Product Weight (Net Weight)			220 kg		
Country of Orig	gin				
Designed, Researched & Developed in			Australia		
Manufactured in			China		
Features					
Rack & Pinion			✓		
Blade Tensioning Quick Release Device			✓		
Induction Motor			✓		
Table Fence Construction			150mm High Aluminium Rip Fence with Solid Round Bar Guide Rail and Solid Cast Locking Mechanism - Fence can be fitted to either side of the work table.		
Mitre Gauge Included			✓		
Push Stick Included			. 🌶		

WWW.BEYONDTOOLS.COM - © COPYRIGHT 2024 BEYOND TOOLS - VERSION: 20241122



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm



Sales Centre for Sales, Advice + Orders T +61 8 9209 7400

hello@beyondtools.com

Tilting Table✓Standard Inclusions1 x Push Stick, 1 x 3962mm Bandsaw Blade, 1 x Mitre GaugePrice VS QualityCommercial (Suitable for Professional / Trade Use)SafetyCommercial (Suitable for Professional / Trade Use)SafetyMagnetic safety switches on all openingsEmergency Stop Switch✓Emergency Stop Mushroom Foot Switch✓Foot Operated Brake✓Blade Guard✓Chuck Guard✓NVR (No Volt Release) Switch✓Rack & Pinion Blade Guide Height Adjustment✓Rack & Pinion Table Angle Adjustment✓Cet Certified✓Dust Port2 x 100mm (4")Workshop (Site) InfoExcludes Plug & Lead (must be connected / installed by Licensed Electrician)Other RequirementsDust ExtractionWarranty1 YearPackaging + Shipping✓Requires a Skid to Ship✓Requires a Skid to Ship✓Requires a Skid to Ship✓Shipping NotesShipping location (Receivers a skid / pallet / crate in order to safely ransport via road.					
Standard Inclusions1 x Push Stick, 1 x 3962mm Bandsaw Blade, 1 x Mitre GaugePrice Vs QualityCommercial (Suitable for Professional / Trade Use)QualityCommercial (Suitable for Professional / Trade Use)SafetyMagnetic safety switches on all openingsEmergency Stop SwitchEmergency Stop SwitchFoot Operated BrakeBlade GuardChuck GuardNVR (No Volt Release) SwitchRack & Pinion Blade Guide Height AdjustmentRack & Pinion Table Angle AdjustmentCE CertifiedDust Port2 x 100mm (4")Workshop (Site) InfoElectrical ConnectionDust ExtractionOther RequirementsDust ExtractionWarranty1 YearPackagingShipping Weight (Gross)245.0 kgPackagingShipping NotesThis product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading limits and requires a skid / pallet / crate in order to	Tilting Table	✓			
QualityCommercial (Suitable for Professional / Trade Use)SafetySafety SwitchMagnetic safety switches on all openingsEmergency Stop SwitchEmergency Stop Mushroom Foot SwitchFoot Operated BrakeBlade GuardChuck GuardNVR (No Volt Release) SwitchRack & Pinion Blade Guide Height AdjustmentRack & Pinion Table Angle AdjustmentCE CertifiedDust Port2 x 100mm (4")Workshop (Site) InfoElectrical ConnectionExcludes Plug & Lead (must be connected / installed by Licensed Electrician)Other RequirementsDust ExtractionWarranty1 YearPackaging + ShippingShipping Weight (Gross)245.0 kgPackagingWooden Box / Crate with SkidRequires a Skid to ShipRequires a Forklift / Tail Lift to UnloadShipping NotesThis product requires a skid / pallet / crate in order to		Bandsaw Blade, 1 x Mitre			
QualityProfessional / Trade Use)SafetyMagnetic safety switches on all openingsEmergency Stop Switch✓Emergency Stop Mushroom Foot Switch✓Foot Operated Brake✓Blade Guard✓Chuck Guard✓NVR (No Volt Release) Switch✓Rack & Pinion Blade Guide Height Adjustment✓Rack & Pinion Table Angle Adjustment✓Ce Certified✓Dust Port2 x 100mm (4")Workshop (Site) Info✓Electrical ConnectionExcludes Plug & Lead (must be connected / installed by Licensed Electrician)Other RequirementsDust ExtractionWarranty1 YearPackaging + Shipping✓Shipping Weight (Gross)245.0 kgPackagingMooden Box / Crate with SkidRequires a Skid to Ship✓Requires a Forklift / Tail Lift to Unload✓Shipping NotesThis product exceeds hand unloading limits and requires a skid / pallet / crate in order to	Price Vs Quality				
Safety SwitchMagnetic safety switches on all openingsEmergency Stop SwitchImage Stop SwitchEmergency Stop Mushroom Foot SwitchImage Stop SwitchFoot Operated BrakeImage Stop SwitchBlade GuardImage Stop SwitchChuck GuardImage Stop SwitchNVR (No Volt Release) SwitchImage Stop SwitchRack & Pinion Blade Guide Height AdjustmentImage Stop SwitchRack & Pinion Table Angle AdjustmentImage Stop Stop Stop Stop Stop Stop Stop Stop	Quality	•			
Safety SwitchopeningsEmergency Stop Switch✓Emergency Stop Mushroom Foot Switch✓Foot Operated Brake✓Blade Guard✓Chuck Guard✓NVR (No Volt Release) Switch✓Rack & Pinion Blade Guide Height Adjustment✓Rack & Pinion Table Angle Adjustment✓CE Certified✓Dust Port2 x 100mm (4")Workshop (Site) InfoElectrical ConnectionElectrical ConnectionDust ExtractionWarrantyJust ExtractionWarranty1 YearPackaging + Shipping245.0 kgPackagingWooden Box / Crate with SkidRequires a Skid to Ship✓Requires a Forklift / Tail Lift to Unload✓Shipping NotesThis product exceeds hand unloading limits and requires a skid / pallet / crate in order to	Safety				
Emergency Stop Mushroom Foot SwitchImage: Constraint of the systemFoot Operated BrakeImage: Constraint of the systemBlade GuardImage: Constraint of the systemChuck GuardImage: Constraint of the systemNVR (No Volt Release) SwitchImage: Constraint of the systemRack & Pinion Blade Guide Height AdjustmentImage: Constraint of the systemRack & Pinion Table Angle AdjustmentImage: Constraint of the systemRack & Pinion Table Angle AdjustmentImage: Constraint of the systemCE CertifiedImage: Constraint of the systemDust Port2 x 100mm (4")Workshop (Site) InfoImage: Constraint of the systemElectrical ConnectionExcludes Plug & Lead (must be connected / installed by Licensed Electrician)Other RequirementsDust ExtractionWarranty1 YearPackaging + ShippingImage: Constraint of the systemShipping Weight (Gross)245.0 kgPackagingImage: Constraint of the systemRequires a Skid to ShipImage: Constraint of the systemShipping NotesThis product exceeds hand unloading limits and requires a sid il filt truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to	Safety Switch	5			
Foot Operated BrakeImage: Section of the	Emergency Stop Switch	✓			
Blade GuardImage: Chuck GuardChuck GuardImage: Chuck GuardNVR (No Volt Release) SwitchImage: Chuck GuardRack & Pinion Blade Guide Height AdjustmentImage: Chuck GuardRack & Pinion Table Angle AdjustmentImage: Chuck GuardRack & Pinion Table Angle AdjustmentImage: Chuck GuardCE CertifiedImage: Chuck GuardDust Port2 x 100mm (4")Workshop (Site) InfoImage: Chuck GuardElectrical ConnectionExcludes Plug & Lead (must be connected / installed by Licensed Electrician)Other RequirementsDust ExtractionWarranty1 YearPackaging + ShippingImage: Chuck GuardShipping Weight (Gross)245.0 kgPackagingWooden Box / Crate with SkidRequires a Skid to ShipImage: Chuck GuardRequires a Forklift / Tail Lift to UnloadImage: Chuck GuardShipping NotesThis product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to	Emergency Stop Mushroom Foot Switch	✓			
Chuck GuardImage: Chuck GuardNVR (No Volt Release) SwitchImage: Guard Guard Height AdjustmentRack & Pinion Blade Guide Height AdjustmentImage: Guard	Foot Operated Brake	✓			
NVR (No Volt Release) SwitchImage: Constraint of the system o	Blade Guard	✓			
Rack & Pinion Blade Guide Height Adjustment✓Rack & Pinion Table Angle Adjustment✓CE Certified✓Dust Port2 x 100mm (4")Workshop (Site) InfoExcludes Plug & Lead (must be connected / installed by Licensed Electrician)Electrical ConnectionDust ExtractionWarrantyDust ExtractionWarranty1 YearPackaging + Shipping245.0 kgPackagingWooden Box / Crate with SkidRequires a Skid to Ship✓Requires a Forklift / Tail Lift to Unload✓Shipping NotesThis product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to	Chuck Guard	✓			
Rack & Pinion Table Angle Adjustment✓CE Certified✓Dust Port2 x 100mm (4")Workshop (Site) InfoExcludes Plug & Lead (must be connected / installed by Licensed Electrician)Electrical ConnectionDust ExtractionOther RequirementsDust ExtractionWarranty1 YearPackaging + Shipping245.0 kgShipping Weight (Gross)245.0 kgPackagingWooden Box / Crate with SkidRequires a Skid to Ship✓Requires a Forklift / Tail Lift to Unload✓Shipping NotesThis product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to	NVR (No Volt Release) Switch	✓			
CE Certified✓Dust Port2 x 100mm (4")Workshop (Site) InfoExcludes Plug & Lead (must be connected / installed by Licensed Electrician)Electrical ConnectionDust ExtractionOther RequirementsDust ExtractionWarranty1 YearPackaging + Shipping245.0 kgPackagingWooden Box / Crate with SkidRequires a Skid to Ship✓Requires a Forklift / Tail Lift to Unload✓Shipping NotesThis product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to	Rack & Pinion Blade Guide Height Adjustment	✓			
Dust Port2 x 100mm (4")Workshop (Site) InfoExcludes Plug & Lead (must be connected / installed by Licensed Electrician)Electrical ConnectionDust ExtractionOther RequirementsDust ExtractionWarranty1 YearPackaging + Shipping245.0 kgShipping Weight (Gross)245.0 kgPackagingWooden Box / Crate with SkidRequires a Skid to Ship✓Requires a Forklift / Tail Lift to Unload✓Shipping NotesThis product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to	Rack & Pinion Table Angle Adjustment	✓			
Workshop (Site) InfoExcludes Plug & Lead (must be connected / installed by Licensed Electrician)Electrical ConnectionExcludes Plug & Lead (must be connected / installed by Licensed Electrician)Other RequirementsDust ExtractionWarrantyI YearPackaging + ShippingImage: Shipping Weight (Gross)Shipping Weight (Gross)245.0 kgPackagingWooden Box / Crate with SkidRequires a Skid to ShipImage: Shipping Weight (Tail Lift to Unload)Shipping NotesThis product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to	CE Certified	✓			
Electrical ConnectionExcludes Plug & Lead (must be connected / installed by Licensed Electrician)Other RequirementsDust ExtractionWarranty1 YearPackaging + Shipping245.0 kgShipping Weight (Gross)245.0 kgPackagingWooden Box / Crate with SkidRequires a Skid to ShipIRequires a Forklift / Tail Lift to UnloadIShipping NotesThis product exceeds hand unloading limits and requires a skid / pallet / crate in order to	Dust Port	2 x 100mm (4")			
Electrical Connectionconnected / installed by Licensed Electrician)Other RequirementsDust ExtractionWarranty1Warranty1 YearPackaging + Shipping245.0 kgShipping Weight (Gross)245.0 kgPackagingWooden Box / Crate with SkidRequires a Skid to Ship✓Requires a Forklift / Tail Lift to Unload✓Shipping NotesThis product exceeds hand unloading limits and requires a skid / pallet / crate in order to	Workshop (Site) Info				
WarrantyI YearWarranty1 YearPackaging + Shipping245.0 kgShipping Weight (Gross)245.0 kgPackagingWooden Box / Crate with SkidRequires a Skid to ShipRequires a Forklift / Tail Lift to UnloadShipping NotesThis product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to	Electrical Connection	connected / installed by			
Warranty1 YearPackaging + Shipping245.0 kgShipping Weight (Gross)245.0 kgPackagingWooden Box / Crate with SkidRequires a Skid to Ship✓Requires a Forklift / Tail Lift to Unload✓Shipping NotesThis product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to	Other Requirements	Dust Extraction			
Packaging + Shipping245.0 kgShipping Weight (Gross)245.0 kgPackagingWooden Box / Crate with SkidRequires a Skid to Ship✓Requires a Forklift / Tail Lift to Unload✓This product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to	Warranty				
Shipping Weight (Gross)245.0 kgPackagingWooden Box / Crate with SkidRequires a Skid to ShipRequires a Forklift / Tail Lift to UnloadThis product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to	Warranty	1 Year			
Packaging Wooden Box / Crate with Skid Requires a Skid to Ship ✓ Requires a Forklift / Tail Lift to Unload ✓ Shipping Notes This product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to	Packaging + Shipping				
Requires a Skid to Ship Image: Constraint of the second secon	Shipping Weight (Gross)	245.0 kg			
Requires a Forklift / Tail Lift to Unload This product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to	Packaging	Wooden Box / Crate with Skid			
Shipping Notes This product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to	Requires a Skid to Ship	✓			
Shipping Notes unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to	Requires a Forklift / Tail Lift to Unload	✓			
	Shipping Notes	unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to			