

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm



Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

SPECIAL ORDER 600MM (24") INDUSTRIAL BANDSAW OPAL TC600 BY TOUGHCUT





Features

Dual 4" Dust Ports
Double Bearing Blade Guide System
Thickened Large Cast Iron Table with T Slot Design
Fully Enclosed thickened Steel Body
Quick Release Blade Tension
Hinged Blade Guard with Sight Window
Rack and Pinion Saw Blade Guide



SKU	Option	Part #	Price
8000908		OPAL TC600	\$5199

Model		
Туре	Bandsaw	
SKU	8000908	
Part Number	OPAL TC600	
Brand	ToughCut	
Size	600mm (24â()	
Technical - Main		
Power Source	415V 50Hz Three Phase	
Bandwheel	Solid Cast Iron Balanced	
Bandwheel Diameter	600 mm	
Blade Length	4470 mm	
Blade Width	10-35mm	
Cutting Capacity - Height	370 mm	
Throat Capacity	580 mm	
Table Size	700 x 608mm	
Technical - Saw		
Blade (Main) - Speed	1500m / Min.	
Country of Origin		
Designed, Researched & Developed in	Australia	
Manufactured in	China	
Features		
Tool Less Blade Guide System	✓	
Blade Tensioning Quick Release Device	✓	
Induction Motor	✓	
Table Fence Construction	150mm High Aluminium Rip Fence with Solid Round Bar Guide Rail and Solid Cast Locking Mechanism - Fence can be fitted to either side of the work table.	
Mitre Gauge Included	✓	
Push Stick Included	✓	
Tilting Table	✓	
Standard Inclusions	1 x Push Stick, 1 x 4470mm Bandsaw Blade, 1 x Mitre Gauge	
Price Vs Quality		
Quality	Commercial (Suitable for Professional / Trade Use)	



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm



Sales Centre for Sales, Advice + Orders T +61 8 9209 7400

hello@beyondtools.com

Safety		
Safety Switch	Magnetic safety switches on a openings	
Emergency Stop Mushroom Foot Switch	✓	
Foot Operated Brake	✓	
NVR (No Volt Release) Switch	✓	
Rack & Pinion Blade Guide Height Adjustment	✓	
Rack & Pinion Table Angle Adjustment	Not Included	
CE Certified	✓	
Dust Port	2 x 100mm (4")	
Workshop (Site) Info		
Electrical Connection	Excludes Plug & Lead (must be connected / installed by Licensed Electrician)	
Other Requirements	Dust Extraction	
Warranty		
Warranty	1 Year	
Use	Intended or designed for commercial use.	
Packaging + Shipping		
Shipping Length	1125 mm	
Shipping Width	780 mm	
Shipping Height	2160 mm	
Shipping Weight (Gross)	317.0 kg	
Packaging	Wooden Box / Crate with Skid	
Requires a Skid to Ship	✓	
Requires a Forklift / Tail Lift to Unload	✓	
Shipping Notes	This product exceeds hand unloading limits and requires tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to safely transport via road.	