

jaccraindustries.com



SPECIAL ORDER 600MM (24") INDUSTRIAL BANDSAW OPAL TC600 BY TOUGHCUT





Features

Dual 4" Dust Ports
Double Bearing Blade Guide System
Thickened Large Cast Iron Table with T Slot Design
Fully Enclosed thickened Steel Body
Quick Release Blade Tension
Hinged Blade Guard with Sight Window
Rack and Pinion Saw Blade Guide



SKU	Option	Part #	Price
8000908		OPAL TC600	\$5199

Model		
Туре	Bandsaw	
SKU	8000908	
Part Number	OPAL TC600	
Brand	ToughCut	
Size	600mm (24â()	
Technical - Main		
Power Source	415V 50Hz Three Phase	
Bandwheel	Solid Cast Iron Balanced	
Bandwheel Diameter	600 mm	
Blade Length	4470 mm	
Blade Width	10-35mm	
Cutting Capacity - Height	370 mm	
Throat Capacity	580 mm	
Table Size	700 x 608mm	
Technical - Saw		
Blade (Main) - Speed	1500m / Min.	
Country of Origin		
Designed, Researched & Developed in	Australia	
Manufactured in	China	
Features		
Tool Less Blade Guide System	✓	
Blade Tensioning Quick Release Device	✓	
Induction Motor	✓	
Table Fence Construction	150mm High Aluminium Rip Fence with Solid Round Bar Guide Rail and Solid Cast Locking Mechanism - Fence can be fitted to either side of the work table.	
Mitre Gauge Included	✓	
Push Stick Included	✓	
Tilting Table	✓	
Standard Inclusions	1 x Push Stick, 1 x 4470mm Bandsaw Blade, 1 x Mitre Gauge	
Price Vs Quality		
Quality	Commercial (Suitable for Professional / Trade Use)	
Safety		
Safety Switch	Magnetic safety switches on all openings	
Emergency Stop Mushroom Foot Switch	✓	
Emergency Stop Mushroom Foot Switch	*	



jaccraindustries.com **TOUGHCUT** Foot Operated Brake NVR (No Volt Release) Switch Rack & Pinion Blade Guide Height Adjustment Rack & Pinion Table Angle Adjustment Not Included **CE** Certified **Dust Port** 2 x 100mm (4") Workshop (Site) Info Excludes Plug & Lead (must be **Electrical Connection** connected / installed by Licensed Electrician) Other Requirements **Dust Extraction** Warranty Warranty 1 Year Intended or designed for Use commercial use. Packaging + Shipping Shipping Length 1125 mm Shipping Width 780 mm Shipping Height 2160 mm Shipping Weight (Gross) 317.0 kg Packaging Wooden Box / Crate with Skid Requires a Skid to Ship Requires a Forklift / Tail Lift to Unload This product exceeds hand unloading limits and requires a tail lift truck or forklift at the

unloading location (Receivers end). This product requires a skid / pallet / crate in order to safely transport via road.

Shipping Notes