

***SPECIAL ORDER* 600MM (24") INDUSTRIAL BANDSAW OPAL TC600 BY TOUGH CUT**



- Features**
- Dual 4" Dust Ports
 - Double Bearing Blade Guide System
 - Thickened Large Cast Iron Table with T Slot Design
 - Fully Enclosed thickened Steel Body
 - Quick Release Blade Tension
 - Hinged Blade Guard with Sight Window
 - Rack and Pinion Saw Blade Guide

SKU	Option	Part #	Price
8000908		OPAL TC600	\$5199

Model	
Type	Bandsaw
SKU	8000908
Part Number	OPAL TC600
Brand	ToughCut
Size	600mm (24")
Technical - Main	
Power Source	415V 50Hz Three Phase
Bandwheel	Solid Cast Iron Balanced
Bandwheel Diameter	600 mm
Blade Length	4470 mm
Blade Width	10-35mm
Cutting Capacity - Height	370 mm
Throat Capacity	580 mm
Table Size	700 x 608mm
Technical - Saw	
Blade (Main) - Speed	1500m / Min.
Country of Origin	
Designed, Researched & Developed in	Australia
Manufactured in	China
Features	
Tool Less Blade Guide System	✓
Blade Tensioning Quick Release Device	✓
Induction Motor	✓
Table Fence Construction	150mm High Aluminium Rip Fence with Solid Round Bar Guide Rail and Solid Cast Locking Mechanism - Fence can be fitted to either side of the work table.
Mitre Gauge Included	✓
Push Stick Included	✓
Tilting Table	✓
Standard Inclusions	1 x Push Stick, 1 x 4470mm Bandsaw Blade, 1 x Mitre Gauge
Price Vs Quality	
Quality	Commercial (Suitable for Professional / Trade Use)
Safety	
Safety Switch	Magnetic safety switches on all openings
Emergency Stop Mushroom Foot Switch	✓
	✓

Foot Operated Brake	
NVR (No Volt Release) Switch	✓
Rack & Pinion Blade Guide Height Adjustment	✓
Rack & Pinion Table Angle Adjustment	Not Included
CE Certified	✓
Dust Port	2 x 100mm (4")
Workshop (Site) Info	
Electrical Connection	Excludes Plug & Lead (must be connected / installed by Licensed Electrician)
Other Requirements	Dust Extraction
Warranty	
Warranty	1 Year
Use	Intended or designed for commercial use.
Packaging + Shipping	
Shipping Length	1125 mm
Shipping Width	780 mm
Shipping Height	2160 mm
Shipping Weight (Gross)	317.0 kg
Packaging	Wooden Box / Crate with Skid
Requires a Skid to Ship	✓
Requires a Forklift / Tail Lift to Unload	✓
Shipping Notes	This product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). This product requires a skid / pallet / crate in order to safely transport via road.