

Unicol Adhesive technologies

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

## **EVA HOT MELT ADHESIVE PELLETS UNIBORD 694 BY UNICOL**





Unicol offers a vast range of hot melt glues which are suitable not only for the types of edge used, but also for the application characteristics of the systems and the degree of resistance and finishing desired. Solid hot-melt adhesive with EVA base for automatic edge-banding machines. EVA hot melt adhesive for softforming is used for gluing solid wood and plastic laminate edges with automatic edge banding machines.

## Applications

Suitable for softforming DIY **Textile Industry** Industrial Adhesives Wood & Furniture Edgebanding **Technical Data sheet** View Data Sheet Here View Unicol Adhesive Catalogue Here Options 694-25KG-BLACK 694-5KG-WHITE 694-25KG-NATURAL 694-25KG-WHITE 694-5KG-NATURAL 694-25KG-WALNUT (NOCE) 694-5KG-BLACK



| SKU     | Option                      | Part #                 | Price |
|---------|-----------------------------|------------------------|-------|
| 8001538 | Colour: Black, Size: 25Kg   | 694-25KG-BLACK         | \$379 |
| 515151  | Colour: Black, Size: 5Kg    | 694-5KG-BLACK          | \$79  |
| 8001536 | Colour: Natural, Size: 25Kg | 694-25KG-NATURAL       | \$379 |
| 9600514 | Colour: Natural, Size: 5Kg  | 694-5KG-NATURAL        | \$84  |
| 8001539 | Colour: Walnut, Size: 25Kg  | 694-25KG-WALNUT (NOCE) | \$379 |
| 8001537 | Colour: White, Size: 25Kg   | 694-25KG-WHITE         | \$379 |
| 8730289 | Colour: White, Size: 5Kg    | 694-5KG-WHITE          | \$84  |
|         |                             |                        |       |

| Model                       |                             |  |
|-----------------------------|-----------------------------|--|
| Туре                        | Hot Melt Adhesive - Pellets |  |
| SKU                         | 8001538                     |  |
| Part Number                 | 694-25KG-BLACK              |  |
| Brand                       | Unicol                      |  |
| Size                        | 25Kg                        |  |
| Technical - Main            |                             |  |
| Colour Name                 | White                       |  |
| Feed Speed                  | 12-30m / Min.               |  |
| Softening Range             | 97-106°C                    |  |
| Temperature on Roller       | 200-220°C                   |  |
| Temperature in Tank         | 170-190°C                   |  |
| Dimensions                  |                             |  |
| Product Weight (Net Weight) | 25 kg                       |  |
| Country of Origin           |                             |  |
| Manufactured in             | Italy                       |  |
| Packaging + Shipping        |                             |  |
| Shipping Weight (Gross)     | 25.0 kg                     |  |