



Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

## 455MM (18") 2HP DELUXE WOOD BANDSAW 240V 10-342 BY RIKON









10-342 is an entry level machine to this larger capacity category. 2HP motor provides plenty of power behind the single 10.5m /min. blade speed of the machine. Cast iron table includes a single 'T' Slot for use with Miter Gauges or other cutting jigs. This powerful bandsaw is outstanding value and a more than capable addition to any workshop.

## Features:-

330mm 13" Cutting Capacity

Patented â€" Spring Loaded Tool-less Guide System

Patented – Quick Adjust 6″ Tall Fence System

Patented â€" Quick Adjust Trunion System

Quick Release Blade Tension

Hinged Blade Guard With Sight Window



| SKU     | Option | Part # | Price  |
|---------|--------|--------|--------|
| 8001745 |        | 10-342 | \$3299 |

| Model                       |  |  |
|-----------------------------|--|--|
| Туре                        | Bandsaw  |  |
| SKU                         | 8001745  |  |
| Part Number                 | 10-342   |  |
| Brand                       | Rikon  |  |
| Size                        | 455mm 18"  |  |
| Technical - Main            |  |  |
| Power Source                | 240V 50Hz Single Phase   |  |
| Motor Power (Input)         | 2HP / 1500W  |  |
| Blade Length                | 3886 mm  |  |
| Blade Width                 | 6-36mm   |  |
| Cutting Capacity - Height   | 330 mm   |  |
| Throat Capacity             | 445 mm   |  |
| Dimensions                  |  |  |
| Product Length              | 970 mm   |  |
| Product Width               | 700 mm   |  |
| Product Height              | 1850 mm  |  |
| Product Weight (Net Weight) | 149 kg   |  |
| Packaging + Shipping        |  |  |
| Shipping Length             | 860 mm   |  |
| Shipping Width              | 570 mm   |  |
| Shipping Height             | 2020 mm  |  |
| Shipping Weight (Gross)     | 185.0 kg   |  |
| Shipping Notes              | This product exceeds hand unloading limits and requires a tail lift truck or forklift at the unloading location (Receivers end). |  |