

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm





200MM (8") WET STONE / WATER COOLED SHARPENER & BUFFER OT-WSS-200 BY OLTRE







The Wet Stone / Water Cooled Sharpener is ideal for putting a precision edge on hand tools blades. Its slow rotation eliminates any chance of ruining edges from overheating. The Buffer is very versatile. With different grades of applied compounds, the wheels can put a quick, final honed edge on tools, or buff a high gloss shine on woods, metals, and other materials. Useful on shop tools, household items, machinery or vehicle parts, sports equipment, and so on.

200mm (8") OT-WSS-200 Wet Stone / Water Cooled Sharpener provides woodworkers with a system that efficiently removes steel and sharpens tool edges without any overheating that can ruin blades, thanks to the slow-turning abrasive wheel and water cooling action. A holding jig makes putting the right cutting angle on tools easy and consistent, every time. Leather strop removes any burrs and puts the final razor-sharp, final honed edge on tools – chisels, plane blades, turning & carving tools, knives, axes, and more.

Features

 $1/4\mbox{HP}$ / $180\mbox{W}$ motor with forward and reverse rotation Steel support bar repositions for horizontal or vertical use with jigs

The jig holds tools and slides along the bar for solid, consistent support

220 grit abrasive wheel will put precision edges on big or delicate tools



SKU	Option	Part #	Price
8001841		OT-WSS-200	\$295

Type SKU 8001841 Part Number OT-WSS-200 Barcode 745240316688 Brand Oltre Size 200mm (8") Technical - Main Power Source 240V 50Hz Single Phase Arbor 12 mm Base Size 292 x 255mm Diameter {"value":200.0,"unit":"mm"} Sanding Disc Size 200 mm Sanding Disc Speed 95RPM Dimensions Product Length 432 mm Product Length 254 mm Product Width 254 mm Product Wight (Net Weight) 10.4 kg Country of Origin Manufactured in China Features Standard Inclusions Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Power Supply Cord Chipping Length 8 mm Shipping Length 9385 mm Shipping Length 970 mm Sentatore Shipping Shipping Length 970 mm Shipping Width 9385 mm Shipping Width 970 mm Shipping Width 9385 mm Shipping Width 9385 mm Shipping Width 9385 mm	Model		
Part Number OT-WSS-200 Barcode 745240316688 Brand Oltre Size 200mm (8") Technical - Main *** Power Source 240V 50Hz Single Phase Arbor 12 mm Base Size 292 x 255mm Diameter {"value":200.0,"unit":"mm"} Sanding Disc Size 200 mm Sanding Disc Speed 95RPM Dimensions *** Product Length 432 mm Product Width 254 mm Product Weight (Net Weight) 10.4 kg Country of Origin *** Manufactured in China Features 1 x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info *** Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping <tr< td=""><td>Туре</td><td colspan="2"></td></tr<>	Туре		
Barcode Brand Oltre Size 200mm (8") Technical - Main Power Source 240V 50Hz Single Phase Arbor 12 mm Base Size 292 x 255mm Diameter {"value":200.0,"unit":"mm"} Sanding Disc Size 200 mm Sanding Disc Speed Dimensions Product Length Product Length Product Weight (Net Weight) Country of Origin Manufactured in Features Standard Inclusions Standard Inclusions Workshop (Site) Info Electrical Connection Packaging + Shipping Shipping Length Packaging + Shipping Shipping Length Power Supply Cord Olite 240V 50Hz Single Phase 240V	SKU	8001841	
Brand Oltre Size 200mm (8") Technical - Main Power Source 240V 50Hz Single Phase Arbor 12 mm Base Size 292 x 255mm Diameter {"value":200.0,"unit":"mm"} Sanding Disc Size 200 mm Sanding Disc Speed 95RPM Dimensions Product Length 432 mm Product Height 305 mm Product Weight (Net Weight) 10.4 kg Country of Origin Manufactured in China Features Standard Inclusions Standard Inclusions Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Pockaging + Shipping Shipping Length Base 2200 mm 240V 50Hz Single Phase 240V 50Hz Sin	Part Number	OT-WSS-200	
Size 200mm (8") Technical - Main Power Source 240V 50Hz Single Phase Arbor 12 mm Base Size 292 x 255mm Diameter { "value":200.0,"unit":"mm"} Sanding Disc Size 200 mm Sanding Disc Speed 95RPM Dimensions Product Length 432 mm Product Width 254 mm Product Weight (Net Weight) 10.4 kg Country of Origin Manufactured in China Features Standard Inclusions Standard Inclusions Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Pockaging + Shipping Shipping Length 8292 x 255mm 240V 50Hz Single Phase 242V 255mm 240V 50Hz Single Phase 242V 255mm 240V 50Hz Single Phase 242V 250nm" 250V 50Hz Single Phase 250Nm" 260V 50Hz Single Phase 2	Barcode	745240316688	
Technical - Main Power Source Arbor 12 mm Base Size 292 x 255mm Diameter {"value":200.0,"unit":"mm"} Sanding Disc Size 200 mm Sanding Disc Speed 95RPM Dimensions Product Length 432 mm Product Width 254 mm Product Weight (Net Weight) 10.4 kg Country of Origin Manufactured in Features 1 x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Brand	Oltre	
Power Source 240V 50Hz Single Phase Arbor 12 mm Base Size 292 x 255mm Diameter { "value":200.0,"unit":"mm"} Sanding Disc Size 200 mm Sanding Disc Speed 95RPM Dimensions Product Length 432 mm Product Weight 305 mm Product Weight (Net Weight) 10.4 kg Country of Origin Manufactured in China Features 1 x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Size	200mm (8")	
Arbor 12 mm Base Size 292 x 255mm Diameter { "value":200.0,"unit":"mm"} Sanding Disc Size 200 mm Sanding Disc Speed 95RPM Dimensions Product Length 432 mm Product Width 254 mm Product Weight (Net Weight) 10.4 kg Country of Origin Manufactured in China Features 1 x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Technical - Main		
Base Size Diameter Evalue":200.0,"unit":"mm"} Sanding Disc Size 200 mm Sanding Disc Speed 95RPM Dimensions Product Length Product Width Product Weight (Net Weight) Country of Origin Manufactured in Features I x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Power Source	240V 50Hz Single Phase	
Diameter { "value":200.0,"unit":"mm"} Sanding Disc Size 200 mm Sanding Disc Speed 95RPM Dimensions Product Length 432 mm Product Width 254 mm Product Weight (Net Weight) 10.4 kg Country of Origin Manufactured in China Features 1 x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig., 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Arbor	12 mm	
Sanding Disc Size 95RPM Dimensions Product Length 432 mm Product Width 254 mm Product Weight (Net Weight) 10.4 kg Country of Origin Manufactured in China Features 1 x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Base Size	292 x 255mm	
Sanding Disc Speed 95RPM	Diameter	{"value":200.0,"unit":"mm"}	
DimensionsProduct Length432 mmProduct Width254 mmProduct Height305 mmProduct Weight (Net Weight)10.4 kgCountry of OriginManufactured inFeatures1 x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing CompoundWorkshop (Site) Info10Amp Lead & PlugElectrical Connection10Amp Lead & PlugPower Supply Cord1.8 mOther RequirementsBenchtopPackaging + Shipping385 mm	Sanding Disc Size	200 mm	
Product Length 432 mm Product Width 254 mm Product Height 305 mm Product Weight (Net Weight) 10.4 kg Country of Origin Manufactured in China Features 1 x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Sanding Disc Speed	95RPM	
Product Width Product Height 305 mm Product Weight (Net Weight) 10.4 kg Country of Origin Manufactured in China Features 1 x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Dimensions		
Product Height 305 mm Product Weight (Net Weight) 10.4 kg Country of Origin Manufactured in China Features 1 x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Product Length	432 mm	
Product Weight (Net Weight) Country of Origin Manufactured in China Features 1 x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Product Width	254 mm	
Country of Origin China Features 1 x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping 385 mm	Product Height	305 mm	
Manufactured in Features 1 x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Product Weight (Net Weight)	10.4 kg	
Features 1 x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Country of Origin		
Standard Inclusions Standard Inclusions Standard Inclusions Standard Inclusions 1 x Wet Grinding Wheel (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Manufactured in	China	
Standard Inclusions Standard Inclusions Standard Inclusions (200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of Honing Compound Workshop (Site) Info Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Features		
Electrical Connection 10Amp Lead & Plug Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Standard Inclusions	(200mm x 40mm x 220G) - Vitrified Aluminium Oxide,, 1 x Leather Stropping Wheel (200mm x 30mm),, 1 x Universal Support Rest (12mm Diameter),, 1 x Water Reservoir,, 1 x Tool Holder Jig,, 1 x Angle Guide,, 1 x Tube of	
Power Supply Cord 1.8 m Other Requirements Benchtop Packaging + Shipping Shipping Length 385 mm	Workshop (Site) Info		
Other Requirements Packaging + Shipping Shipping Length Benchtop 385 mm		10Amp Lead & Plug	
Packaging + Shipping Shipping Length 385 mm	Power Supply Cord	1.8 m	
Shipping Length 385 mm	·	Benchtop	
	Packaging + Shipping		
Shipping Width 370 mm	Shipping Length	385 mm	
	Shipping Width	370 mm	



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm







Large, removable water tray for easy refilling and clean-up Rugged plastic cabinet keeps motor safe from moisture Leather honing wheel for final edge sharpening and honing Protected switch with Forward ON & Reverse ON / OFF positions

Shipping Height	360 mm
Shipping Weight (Gross)	11.8 kg
Packaging	Cardboard Box