

420MM PNEUMATIC ALUMINIUM, PVC & WOOD PROFILE UP CUTTING SAW MACHINE 415V FN 420AC BY FEN-IS *SPECIAL ORDER*



FN 420AC Automatic Up-Cutting Saw Machine is used for straight and angular cutting operations of aluminum, wooden and plastic materials. The machine can be used the lateral cutting mode and longitudinal cutting mode.

Features

Hydro-Pneumatic cutting process

- Cutting speed adjustment based on the profile
- Safety cutting with safeguard system
- Cutting at any desired angle between -90°, +45° and 15°, 22.5°, 30°, 45°, 60°, 67.5°, 75° ve 90° right and left angle fixing.
- It has the ability of lateral and longitudinal cutting operations
- with 180° rotary plate Increase in cutting capacity with mobile mitre
- Pneumatic vertical and horizontal clamps
- Changing the saw blade ease
- Standard Equipment

Ø420mm saw blade

2x pneumatic vertical clamps 2x pneumatic horizontal clamps 2x pneumatic horizontal clamps Cooling system Back fence FN 3000K Manual Conveyor (right) **Options** FN 3000K / FN 3000DK Conveyor Single-phase system



SKU	Option	Part #	Price	
8043154		FN 420AC	\$8999	
Model				
Туре		Up Cutti	ng Saw Machine	
SKU			8043154	
Part Number		FN 420A	FN 420AC	
Brand		Fen-Is	Fen-Is	
Size		420mm		
Technical - Main				
Power Source		415V 50	Hz 3 Phase	
Motor Power (Input)		3HP 220	3HP 2200W	
Air Supply (CFM)		6-8 Bar	6-8 Bar	
Motor Speed - No Load		3000RPM	3000RPM	
Options		Motor Br	Motor Brake Unit (Optional)	
Technical - Saw				
Blade (Main) - Bore Siz	e (mm)	30-32mr	30-32mm	
Blade (Main) - Diamete	er (Max.)	400 mm	400 mm	
Blade (Main) - Speed		3000RPN	3000RPM	
Country of Origin				
Manufactured in		Turkey	Turkey	
Features				
Standard Inclusions		pneumat pneumat Cooling s	 Ã 420mm saw blade, 2x pneumatic vertical clamps, 2x pneumatic horizontal clamps, Cooling system, Back fence, FN 3000K Manual Conveyor (right) 	
Workshop (Site) Info)			
Air Supply (CFM)		6-8 Bar	6-8 Bar	
Other Requirements		Compres	Compressed Air	
Warranty				
Warranty		1 Year		
Packaging + Shippir	g			
Shipping Weight (Gross)		184.0 kg	184.0 kg	
Shipping Notes		pallet / c	This product requires a skid / pallet / crate in order to safely transport via road.	