

RESAW POWER FEEDER 240V TC-PF-R-AF06 BY TOUGH CUT *NEW ARRIVAL*



SKU	Option	Part #	Price
8043419		TC-PF-R-AF06	\$1950



Model	
Type	Power Feeder
SKU	8043419
Part Number	TC-PF-R-AF06
Brand	ToughCut
Technical - Main	
Power Source	240V 50Hz Single Phase
Speed Range	5m / min., 6.5m / min., 11m / min., 8m / min.
Dimensions	
Product Weight (Net Weight)	17.5 kg
Country of Origin	
Manufactured in	Taiwan
Warranty	
Warranty	1 Year
Packaging + Shipping	
Shipping Length	584 mm
Shipping Width	390 mm
Shipping Height	273 mm
Shipping Weight (Gross)	19.5 kg

The TC-PF-R-AF06 Resaw Power Feeder is an unmatched, highly efficient feeder specially designed for light to medium use on a bandsaw.

Features

1/8 HP Motor (90W)

2 Rollers - 200mm Diameter x 25mm - Polyurethane Coated Rollers

Speeds - 1.5-12 M/min

Safety at Your Fingertips - By keeping your hands away from cutting edges.

Specification

Distance required from mounting position on corner of table to tip of blade: 370mm to 469mm (14.5" to 18.5")

May need to add extension if too small

Maximum Height of Rollers: 82mm (3-3/8")

Maximum Roller-Blade Clearance: 246-398mm (9-1/2") (15-1/2")

Made for Resaws and Bandsaws

This special purpose feeder is designed for bandsaws between 20" and 24" (500 - 600mm) and is ideal for light to medium-duty use. Its multi-step adjustable arm design makes this feeder compatible with the majority of band resaws. It is spring-loaded, ensuring smooth and accurate cuts. The distance required from mounting position on corner of table to tip of blade is 370mm to 469mm (14.5" to 18.5"), may need to add extension if too small.

Variable Speed



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com



Speed settings can be easily adjusted according to your requirements. With variable speed adjustment ranging from 1.5-12 M/min (5-40 FPM), the TC-PF-R-AF06 provides a range of speed options for your stock feeding needs.

Drill-less Fast Positioning Design

No need to drill holes in your bandsaw, you only need to use the parts that come with the feeder to secure it to the bandsaw.

Adjustable Rollers

The rollers can be adjusted according to your feeding needs. The maximum height of the rollers is 82mm (3-3/8").