



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

## 1/2" 120XP FLEX HEAD ELECTRONIC TORQUE WRENCH WITH ANGLE 85196 BY GEARWRENCH



SKU	Option	Part #	Price
8300600		85196	\$609



Model	
Type	Digital Torque Wrench
SKU	8300600
Part Number	85196
Barcode	099575851964
Brand	GearWrench
Size	1/2"
Technical - Main	
Material	Full Polish Chrome
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

### Features:

120XP™ head provides a 3 ° ratcheting arc to turn fasteners in narrow spaces  
Low profile tube, 15 ° flex teardrop head, and flush mounted on/off switch allow for better access in tight confines  
Digitally tracks torque and angle measurements. Vibrating handle, buzzer, and LCD screen alert when target torque is reached  
3 function modes feature peak torque, angle, and peak angle for additional versatility  
5 torque measurement units provide a readout in ft-lb, in-lb, Nm, Kg-m, and Kg-cm  
10 available preset torque settings allow you to quickly access frequently repeated applications  
Torque accuracy of +/-2% CW and +/-3% CCW between 20% and 100% of wrench capability Angle settings offer +/-1% of reading of angle accuracy  
Knurled aluminum handle lets you grip comfortably, while clearly marked midpoint promotes additional accuracy  
Meets or exceeds ASME standards and specifications  
1 year limited warranty; calibration accuracy warrantied for 90 days

### Specifications:

Overall Length 23.7 in  
ASME Specification B107.10 B107.12 B107.28 B107.300  
Drive Type Square  
Drive Tang Size 1/2 in  
Knurled Yes  
Tooth Count 120XP™  
Head Thickness .93 in  
Head Width 1.73 in  
Finish Full Polish Chrome



**23 Exhibition Drive, Malaga Western Australia**

Monday - Friday 7am-5pm + Sat 8am-4pm

**Sales Centre** for Sales, Advice + Orders

T +61 8 9209 7400

[hello@beyondtools.com](mailto:hello@beyondtools.com)

Min Torque (Primary Scale) 25 ft/lb

Max Torque (Primary Scale) 250 ft/lb

Alt Scale Increments .1 Nm

Primary Scale Increments .1 ft/lb

Min Torque (Alt Scale) 34 Nm

Max Torque (Alt Scale) 340 Nm

Head Thickness Less Tang .74 in

Torque Accuracy (20-100% of Full Range) +/-2% Clockwise

Head Length 2.65 in

Material Alloy Steel

**Includes:**

Calibration certificate

Blow mould case