

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

230MM 2400W ANGLE GRINDER WE 24-230 MVT QUICK (606470190) BY METABO



SKU	Option	Part #		Price
8400179		606470	190	\$379
Model				
Туре			Angle Grinder	
SKU			8400179	
Part Number			606470190	
Barcode			4007430268235	
Brand			Metabo	
Technical - Main				
Motor Speed - No Load			6600 rpm	
Dimensions				
Product Weight (Net Weight)			5.8 kg	
Packaging + Shipping				
Shipping Weight (Gross)			1.48 kg	





Metabo Marathon motor with patented dust protection for long service life

Electronic safety shutdown: reduces kickback if the disc stops unexpectedly - for high user safety

Deadman's switch for high user protection

Rotating back handle and side handle can be mounted at 3 positions for optimum handle position also when cutting Metabo Quick for tool-free disc change by means of a quick-

locking nut

Tool-free adjustable guard; twist-proof

Starting current limitation prevents the actuation of the lock on start-up

Electronic overload protection and restart protection Metabo VibraTech (MVT): integrated damping system and side handle to reduce vibrations in order to protect the user's health

Metabo safety switch prevents unintentional start

Auto-stop carbon brushes to protect the motor LED signal indicates triggered restart protection or

overheating

The machine shown may differ in equipment and technical details depending on the configuration.

Specifications:

Grinding wheel Ã[~]: 230 mm / 9 " Rated input power: 2400 W Output power: 1600 W No-load speed: 6600 rpm Revolutions at rated load: 4600 rpm



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

Torque: 17 Nm / 150 in-lbs Spindle thread: M 14 Weight (without power cable): 5.8 kg / 12.8 lbs Cable length: 4 m / 13 ft Vibration: Surface grinding: 6.2 m/s ² Uncertainty of measurement K: 1.5 m/s ² Grinding with sandpaper: 2.5 m/s $^{\rm 2}$ Uncertainty of measurement K: 1.5 m/s ² Noise emission: Sound pressure level: 94 dB(A) Sound power level (LwA): 105 dB(A) Uncertainty of measurement K: 3 dB(A) Includes: Guard Inner Support Flange

M-Quick flange nut Metabo VibraTech (MVT) side handle