


124MM SOLID CONTROL HANDWHEEL WITH FOLDAWAY HANDLE & LOCKING KNOB C990125.TP0501P BY BOTECO



SKU	Option	Part #	Price
8415		C990125.TP0501	\$49

Model	
Type	Spare Parts - Handwheel
SKU	8415
Part Number	C990125.TP0501
Brand	Boteco
Size	124mm
Technical - Main	
Colour Name	Black
Diameter	124mm
Finish	Satin
Material	Reinforced Polyamide. (Oil and grease resistant)
Dimensions	
Product Length	124 mm
Product Width	124 mm
Product Height	48 mm
Product Weight (Net Weight)	0.41 kg
Country of Origin	
Manufactured in	Italy
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg

Specifications:-
Materials: Reinforced and stabilized polyamide. Resistant to oils and greases.
Surface finish: Satin.
Handwheel and handle colour: Black (RAL 9011).
Central cap: Grey polyamide (RAL 7035 code 13).
Main insert: Galvanised steel insert with smooth through bore (tolerance H10).
Lateral insert: Brass insert with threaded through hole.
Lateral handle: Revolving handle that folds into the handwheel, with hexagonal connection. Reinforced polyamide handle. Black-oxide treated internal mechanism. Fixed with black-oxide treated hexagon socket button head screw ISO 7838.
Locking knob: Black cylindrical knob Ral 9011 art. G793-36 with threaded stud [pageFAM_G793-Codice. Caution: the R and Q2 dimensions of the locking knob must be chosen by the customer according to the dimensions of the machinery on which the solid handwheel will be installed.
Fixing method: For fixing systems, or execution of keyways or square holes, please refer to the technical notes attached to the catalogue [pageFAM_NT10-Codice

Dimensions (refer image):-																		
Art.	D	H	Ht	h	d	m	c	d3	h3	R	d2	Q2	dI	L	Dm	d1	H10	Q
C990125.TP0501P	124	48	49.5	40	36	21.5	26.5	16	15	22	25	M6	A.R.	20	38	18	05	24 410
C990150.TD0801P	149	53	-	44	38	24.5	28.5	12	26	25	28	M8	A.R.	20	58	22	08	32 560
C990175.TD0801P	174	58	-	48	40	24.5	33.5	16	26	26	36	M8	A.R.	26	80	28	08	32 775
C990200.TD0801P	198	63	-	53	44	24.5	38.5	17	26	28	42	M8	A.R.	27	90	28	08	36 1075
C990250.TD0801P	250	67	-	58	60	29	38	22	36	36	50	M8	A.R.	27	90	28	08	36 1560

Technical Data:-

