

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm




Sales Centre for Sales, Advice + Orders T+61 8 9209 7400 hello@beyondtools.com

VACUUM PRESS (DOUBLE TABLE) ROBO BY RIBEX









Vacuum Press (Double Table) ROBO by Ribex, Manufactured in Turkey

New generation RIBEX Vacuum Press Machines are used for flat or 3D lamination of pvc foils to MDF board, Chipwood, Plywood e.t.c and suitable for doors and cabinets, panels in kitchens, various furniture applications, in bathrooms and bedrooms. Process starts by heating cycle with high temperature quartz heating elements then gradually vacuum press cycle to finish foiling with negative suction pressure. Optional silicone membrane allows to also laminate veneers as well as the other laminating products onto the workpiece. Moreover this, ROBO has a unique full automatic touchscreen PLC system, cooling fans system boosting your production speed at your maximum limits.

Features:-

4-5 Minutes Total Operating Time **Automatic Temperature Control Double Table Selection** Low Cost Heating Elements Ergonomic body design Full Automatic LG LS PLC System CE, ISO 9001 certified products Work table security sensors Automatic temperature control Options to Single or Dual table control Short operation time Independent vacuum and temperature system Viewing window for viewing workpiece during operation

Model	
Туре	Vacuum Press
SKU	8600494
Part Number	RIBEX ROBO
Brand	Ribex
Technical - Main	
Power Source	415V 50Hz 3 Phase
Motor Power (Input)	3HP 2200W
Table Size	2710 x 1230mm
Dimensions	
Product Length	3400 mm
Product Width	5300 mm
Product Height	1850 mm
Product Weight (Net Weight)	1750 kg
Workshop (Site) Info	
Electrical Connection	Excludes Plug & Lead (must be connected by Licensed Electrician)
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm



Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

Manual setting and usage Low-cost maintenance/repair Low cost heater Removable control table

Different language selection
Minimum wastage and saving from time

Thermofoil PVC stand

Specifications:-

Working Table Area: 2275x1230mm

Pump Motor Speed: 1450rpmPump Motor Speed: 1.5kw

Total Power: 47kw Weight: 750kg

O/A Dimensions: 3000 x 3000 x 1400mm

Specifications:-

Table Frame Dimension : 2870 * 1440 mmTable Usage Area : 2710 * 1230 mm

Maximum Working Thickness : 90 mm Pump Motor Power : 2,2 Kw : 1450 d/dk Pump Motor Speed Pump Extraction Capacity : 105m 3 / h Noise Limit : 68 Dba : 200 ° C Max Temprature Total Power : 26.5 Kw **Total Operation Time** : 4 - 5 Min. : 1350 Kg Average Weight Single Table Average Weight Double Table : 1750 Kg

Dimensions Single Table (WxLxH): 3400*3600*1850 mm Dimensions Double Table (WxLxH): 3400*5300*1850 mm

Options:-

Robo Magnetic System for support the workpiece on

worktable

Divisible Table to use material economize.

Second table preparation for single table machines

Extra Thermofoil PVC stand Silicone membrane unit PLC controlling system