

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

1700W SDS-MAX COMBINATION HAMMER KHE96 (600596000) BY METABO





8700501	Option	KHE96	\$1369	
0700301		KILSO	Ψ1303	
Model				

Model	
Туре	Rotary Hammer
SKU	8700501
Part Number	KHE96
Barcode	4007430167088
Brand	Metabo
Dimensions	
Product Weight (Net Weight)	11.8 kg
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg



Description:

Combination hammer with 2 functions: hammer drilling and chiselling

Metabo VibraTech (MVT): integrated damping system to reduce vibrations in order to protect the user's health Vario-Tacho-Constamatic (VTC)-Full Wave Electronics for work with materials requiring customised speeds, which remain constant under load

Thumbwheel for preselection of the speed and impact rate Electronic soft start for precise spot-drilling

 $\label{thm:conditional} \mbox{Metabo S-automatic safety clutch: mechanical decoupling of the drive for safe working should the drill stop unexpectedly \end{tabular}$

Wear Indication for Carbon Brush

Lockable switch for comfortable working in continuous operation

Specifications:

Max. single blow energy (EPTA): 20 J Maximum impact rate: 1950 bpm Rated input power: 1700 W

Drill- \tilde{A}^{\sim} concrete with hammer drills: 50 mm / 2 " mm

No-load speed: 125 - 250 rpm

Bit retainer: SDS-max

Collar diameter: 73 mm / 2 7/8 " mm

Weight (without power cable): 11.8 kg / 26 lbs kg

Cable length: 6 m / 20 ft

Vibration:



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

Hammer drilling concrete: 12.4 m/s $^{\rm 2}$ Uncertainty of measurement K: 2 m/s $^{\rm 2}$

Chiseling: 11 m/s ²

Uncertainty of measurement K: 2 m/s ²

Noise Emission:

Sound pressure level: 100 dB(A) Sound power level (LwA): 111 dB(A) Uncertainty of measurement K: 3 dB(A)

Includes:

Metabo VibraTech (MVT) side handle

Lubricant for tool shank end

Duster

Plastic carry case