

18V 125MM FLAT-HEAD ANGLE GRINDER BARE (TOOL ONLY) WF18LTX125QUICK (601306840) BY METABO



SKU	Option	Part #	Price
8703328		601306840	\$379

Model	
Type	Angle Grinder
SKU	8703328
Part Number	601306840
Barcode	4007430287182
Brand	Metabo
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg



Features:

- Extremely flat gear head permits working within acute angles down to 43 °
- Compact design for quick removal of welding slag, rust or paint in tight places e.g. frame constructions
- Low-fatigue working even on weld seams in difficult to access places thanks to slim handle
- Robust motor for long service life
- Metabo Quick for tool-free disc change by means of a quick-locking nut
- Tool-free adjustable guard; twist-proof
- Battery pack can be swivelled for better working in hard to reach places
- Detachable dust filter protects motor from coarse particles
- Overload protection: protects the motor from overheating
- Electronic soft start for smooth start-up
- Restart protection: prevents unintentional start-up after battery pack change
- Ultra-M technology: highest performance, gentle charging and 3 years of warranty on the battery pack.
- Battery packs with capacity display for checking the charge status

Includes:

- 5 Flap discs Flexiamant Super Convex (125mm; P60)
- Guard
- Inner support flange
- Quick-locking nut
- Side handle



23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders

T +61 8 9209 7400

hello@beyondtools.com

Dust protection filter

MetaLoc case

without battery pack, without charger

Specifications:

Battery voltage: 18 V

Minimum accessible angle: 43 °

Grinding wheel $\tilde{\text{A}}$: 125 mm / 5 "

No-load speed: 8000 rpm

Spindle thread: M 14

Weight (including battery pack): 2.4 kg / 5.3 lbs

Vibration

Surface grinding: 4.5 m/s²

Uncertainty of measurement K: 1.5 m/s²

Grinding with sandpaper: 2.5 m/s²

Uncertainty of measurement K: 1.5 m/s²

Noise emission

Sound pressure level: 83 dB(A)

Sound power level (LwA): 94 dB(A)

Uncertainty of measurement K: 3 dB(A)