

23 Exhibition Drive, Malaga Western Australia

Monday - Friday 7am-5pm + Sat 8am-4pm

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

25/64" BRIGHT CARDED HSS JOBBER DRILL BIT 2006-25/64S BY BORDO





BORDO METRIC QUICK SILVER M2 HSS JOBBER DRILLS

ANSI B94-11 118 ° Split Point (crankshaft point) Split point is self centering and reduces the need for end thrust. Friction at workpiece is reduced. 118 º point angles are ideal for use in materials such as mild steel and cast iron. The 118 $^{\circ}$ point creates easily controlled chips which are wide and thin.

DRILL BIT SURFACE TREATMENT Bright Finish Jobber Drills have no surface treatment and are supplied in the as-ground condition. These tools are suitable for general purpose use, particularly for non-ferrous applications. Specifications:

Spindle Speed Stainless Steel RPM: 385 Spindle Speed Tool Steel RPM: 578 Spindle Speed Cast Iron RPM: 771 Spindle Speed Malleable Iron RPM: 867 Spindle Speed Med. Carbon Steel RPM:963 Spindle Speed Free Cutting Steel RPM: 1381 Spindle Speed Aluminium/Brass RPM: 1959 Spindle Speed Wood/Plastic RPM: 2922 Feed per revolution mm: 0.2



SKU	Option	Part #	Price
8703504		2006-25/64S	\$12.4

Model		
Туре	Drill Bit	
SKU	8703504	
Part Number	2006-25/64S	
Barcode	9326518035831	
Brand	Bordo	
Size	25/64"	
Technical - Main		
Flute Length	95mm	
Workshop (Site) Info		
Flute Length	95mm	
Packaging + Shipping		
Shipping Weight (Gross)	1.48 kg	
Quantity Per Pack	1	