

Sales Centre for Sales, Advice + Orders T +61 8 9209 7400 hello@beyondtools.com

29/64" BRIGHT CARDED HSS JOBBER DRILL BIT 2006-29/64S BY BORDO



BORDO METRIC QUICK SILVER M2 HSS JOBBER DRILLS ANSI B94-11 118 ° Split Point (crankshaft point) Split point is self centering and reduces the need for end thrust. Friction at workpiece is reduced. 118 ^o point angles are ideal for use in materials such as mild steel and cast iron. The 118 ° point creates easily controlled chips which are wide and thin. **DRILL BIT SURFACE TREATMENT** Bright Finish Jobber Drills have no surface treatment and are supplied in the as-ground condition. These tools are suitable for general purpose use, particularly for non-ferrous applications. Specifications: Spindle Speed Stainless Steel RPM: 332 Spindle Speed Tool Steel RPM: 498 Spindle Speed Cast Iron RPM: 664 Spindle Speed Malleable Iron RPM: 747 Spindle Speed Med. Carbon Steel RPM:830 Spindle Speed Free Cutting Steel RPM: 1190 Spindle Speed Aluminium/Brass RPM: 1688 Spindle Speed Wood/Plastic RPM: 2518 Feed per revolution mm: 0.22



SKU	Option	Part #	Price
8703508		2006-29/64S	\$15.6

Model	
Туре	Drill Bit
SKU	8703508
Part Number	2006-29/64S
Barcode	9326518035879
Brand	Bordo
Size	29/64"
Technical - Main	
Flute Length	106mm
Workshop (Site) Info	
Flute Length	106mm
Packaging + Shipping	
Shipping Weight (Gross)	1.48 kg
Quantity Per Pack	1